



USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Reno	Fraction 10 1/4 NW 1/4 SW 1/4	Section number 8	Township number T 24 S R 6 E/W	Range number
2. Distance and direction from nearest town or city: Street address of well location if in city:		2 1/2 So of white side 1/4 cor in field		3. Owner of well: R.R. or street: City, state, zip code:		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 26 in. Completion date 7/30/77 Well depth 52 ft.		
				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
5. Type and color of material		From	To	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Brown clay		0	5	9. Casing: Material Transite Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface <input checked="" type="checkbox"/> 8 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 30 lbs./ft. Dia. 16 in. to 26 ft. depth Wall Thickness: inches or Dia. 0 in. to 26 ft. depth gage No. 3/16		
Brown clay to light brn. sandy clay		5	10	10. Screen: Manufacturer's name Johnson Type sawed Dia. 16 Slot/gauze 3/16 Length 32 Set between 26 ft. and 32 ft. ft. and 32 ft.		
Fine sand & little clay		10	15	Gravel pack? yes Size range of material 1/8-1/4		
Med. to fine sand		15	25	11. Static water level: 28 ft. below land surface Date 7/30/77		
Fine sand & clay		25	30	12. Pumping level below land surfaces: 38 ft. after 1 hrs. pumping 180 g.p.m. ft. after 1 hrs. pumping 180 g.p.m. Estimated maximum yield 180 g.p.m.		
Med. sand & clay		30	35	13. Water sample submitted: mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date 7/30/77		
Med. sand		35	40	14. Well head completion: Y Pitless adapter Y Inches above grade		
Med. sand & clay		40	45	15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
Brown sandy clay		45	55	16. Nearest source of possible contamination: ft. None Direction None Type None Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Dark brn. sandy clay to shale		55	57	17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Darling Model number 189 HP 1 Volts 115 Length of drop pipe 10 ft. capacity 180 g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation: 1571		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Darling Drilling Co. 189 Business name License No. 111 Address 111 W. 4th Hutchinson, Kan Signed Darling Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-8