


1 LOCATION OF WATER WELL: County: Leaw Fraction: SW 1/4 NW 1/4 NW 1/4 Section Number: 8 Township Number: 24 S Range Number: 6 E/W

Distance and direction from nearest town or city street address of well if located within city? 1 1/2 mi S of Whiteside

2 WATER WELL OWNER: Roman Beachy RR#, St. Address, Box #: Rt 1 City, State, ZIP Code: Hutch, KS 67501 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 53 ft. ELEVATION: 2-14-85

Depth(s) Groundwater Encountered 1. 27 ft. 2. 29 ft. 3. 30 ft. WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 2-14-85

Pump test data: Well water was 29 ft. after 2 hours pumping 30 gpm Est. Yield 50 gpm: Well water was 29 ft. after 2 hours pumping 30 gpm Bore Hole Diameter 10 in. to 56 ft. and 56 in. to 56 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threated

Blank casing diameter 6 in. to 43 ft. Dia 3.35 in. to 160 lbs./ft. Wall thickness or gauge No. 160

Casing height above land surface 24 in. weight 3.35

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 43 ft. to 53 ft. From 35 ft. to 56 ft. GRAVEL PACK INTERVALS: From 35 ft. to 56 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? S How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	1	Top Soil			
1	6	Br Clay			
6	32	Sand & Clay silt			
32	56	Sand & Sm Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-15-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 3-6-85 under the business name of Miller Drilling by (signature) Ken Miller

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.