

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Reno	Fraction NW 1/4 NW 1/4 NE 1/4	Section number 8	Township number T 24 S R 6 E	Range number 6															
2. Distance and direction from nearest town or city: 25 3 1/2 W of			3. Owner of well: Alva Miller																		
Street address of well location if in city: So. Hutchinson, Ks			City, state, zip code: Hutchinson, Ks 67501																		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 10 in. Completion date 4-26-76																	
				Well depth 45 ft.																	
				7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary																	
5. Type and color of material				8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry																	
				<input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																	
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td>Black Top soil</td> <td>0</td> <td>2</td> </tr> <tr> <td>Brown sandy clay</td> <td>2</td> <td>7</td> </tr> <tr> <td>Clay - Brown</td> <td>7</td> <td>20</td> </tr> <tr> <td>Sand - coarse - yellow</td> <td>20</td> <td>45</td> </tr> </tbody> </table>					From	To	Black Top soil	0	2	Brown sandy clay	2	7	Clay - Brown	7	20	Sand - coarse - yellow	20	45	9. Casing: Material PLST Height: Above or below		
					From	To															
Black Top soil	0	2																			
Brown sandy clay	2	7																			
Clay - Brown	7	20																			
Sand - coarse - yellow	20	45																			
				Threated <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in.																	
				RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 195 lbs./ft.																	
				Dia. 6 in. to 45 ft. depth Wall Thickness: inches or																	
				Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 200																	
				10. Screens: Manufacturer's name J+L																	
				Type RMP Dia. 6"																	
				Slot/gauze 3/32 Length 10'																	
				Set between 33 ft. and 45 ft.																	
				Gravel pack? <input checked="" type="checkbox"/> Size range of material E-12																	
				11. Static water level: 28 ft. below land surface Date 4-2-76																	
				12. Pumping level below land surfaces:																	
				30 ft. after 1 hrs. pumping 20 g.p.m.																	
				ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m.																	
				Estimated maximum yield 50 g.p.m.																	
				13. Water sample submitted: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Date 4-2-76																	
				14. Well head completion:																	
				<input checked="" type="checkbox"/> Pitless adapter <input type="checkbox"/> inches above grade																	
				15. Well grouted? yes																	
				With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete																	
				Depth: From 4 ft. to 14 ft.																	
				16. Nearest source of possible contamination:																	
				ft. 60 Direction SW Type septic																	
				Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No																	
				17. Pump:																	
				<input type="checkbox"/> Not installed																	
				Manufacturer's name Aermotor																	
				Model number SDA 75 HP 3/4 Volts 230																	
				Length of drop pipe 35 ft. capacity 19 g.p.m.																	
				Type:																	
				<input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine																	
				<input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating																	
				<input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																	
18. Elevation:		19. Remarks:		20. Water well contractor's certification:																	
Topography:				This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.																	
<input type="checkbox"/> Hill				Miller Water Well Serv. 137																	
<input type="checkbox"/> Slope				Business name Hutchinson, Ks. License No.																	
<input checked="" type="checkbox"/> Upland				Address Hutchinson, Ks.																	
<input type="checkbox"/> Valley				Signed Joe Miller Date 6-10-76																	
				Authorized representative																	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5