

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>SE 1/4 NE 1/4 NE 1/4</u>	<u>10</u>	<u>T 24 S</u>	<u>R 6 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>3 miles, 1 W of S. Hutch - 6513 S Valley Pride Rd</u>					
2 WATER WELL OWNER: <u>Glendon Jones</u>					
RR#, St. Address, Box # : <u>6513 S Valley Pride</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Hutch, KS 67501</u>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>55</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>20</u> ft. below land surface measured on mo/day/yr <u>3-14-92</u>			
		Pump test data: Well water was <u>24</u> ft. after <u>1/2</u> hours pumping <u>30</u> gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8</u> in. to <u>58</u> ft., and in. to ft.			
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes..... No ☒ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	
☒ PVC		4 ABS	7 Fiberglass		
Blank casing diameter <u>5</u> in. to <u>45</u> ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface <u>12</u> in., weight <u>2.37</u> lbs./ft. Wall thickness or gauge No. <u>160</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL: ☒ PVC 10 Asbestos-cement					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	☒ Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>45</u> ft. to <u>55</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>22</u> ft. to <u>30</u> ft., From ft. to ft.					
From <u>35</u> ft. to <u>58</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ Bentonite 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>22</u> ft., From <u>30</u> ft. to <u>35</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:					
☒ Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	
Direction from well? <u>N-NW</u> How many feet? <u>110</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>12</u>	<u>Br + Gr clay</u>			
<u>12</u>	<u>28</u>	<u>Sand + Gravel</u>			
<u>28</u>	<u>39</u>	<u>Br clay</u>			
<u>39</u>	<u>45</u>	<u>F Sand</u>			
<u>45</u>	<u>55</u>	<u>Sand + Gravel</u>			
<u>55</u>	<u>58</u>	<u>Br clay</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-14-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>5-31-92</u> under the business name of <u>Miller Drilling</u> by (signature) <u>Eg Miller</u>					