

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>SE 1/4 SE 1/4 SW 1/4</u>	<u>36</u>	<u>T 24 S</u>	<u>R 7 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>2 mi. N, 2 1/2 E of Partridge - 7412 W Morgan Ave</u>					
2 WATER WELL OWNER: <u>Harvey Nisly</u>					
RR#, St. Address, Box # : <u>9516 W Morgan Rd</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Partridge, KS 67566</u>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>70</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>39</u> ft. below land surface measured on mo/day/yr <u>8-28-98</u>			
		Pump test data: Well water was <u>47</u> ft. after <u>1</u> hours pumping <u>25</u> gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8</u> in. to <u>7 1/4</u> ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		<input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <input checked="" type="radio"/> PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 2 Fiberglass Threaded					
Blank casing diameter <u>5</u> in. to <u>60</u> ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface <u>12</u> in. weight <u>2.29</u> lbs./ft. Wall thickness or gauge No. <u>160</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped <input checked="" type="radio"/> Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>60</u> ft. to <u>70</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>23</u> ft. to <u>56</u> ft. From ft. to ft.					
From <u>59</u> ft. to <u>74</u> ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <input checked="" type="radio"/> Bentonite 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>23</u> ft. From <u>56</u> ft. to <u>59</u> ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool <input checked="" type="radio"/> Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>W</u>		How many feet? <u>300</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>27</u>	<u>Gr. Clay</u>			
<u>27</u>	<u>56</u>	<u>F-C Sand</u>			
<u>56</u>	<u>60</u>	<u>Br Clay</u>			
<u>60</u>	<u>74</u>	<u>Sand & sm Gravel</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="radio"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-28-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>114</u> This Water Well Record was completed on (mo/day/yr) <u>9-16-98</u> under the business name of <u>Miller Drilling</u> by (signature) <u>Eg Miller</u>					