WATE	R WEL	L RECORD	Form W	WC-5	Division of Wa	ter Resources App. N	0. 47,301	
1 LOC	CATION	OF WATER WELL:	Fraction		Section Number	, ,	Range Number	
Cour	nty: Ren	0	NW 1/4 NE 1/4 NW	/ 1/4 SW 1/4	21	T 24 S		
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:								
from	nearest t	own or intersection: If at	owner's address, check	Latitude: 37.94801 (in decimal degrees)				
From Partridge, Ks. 4 1/2 S 1 W 1/2 N					Longitude: 098.10182 (in decimal degrees) Elevation: 1604			
						84, 🔲 NAD 83, 🔼		
		ELL OWNER: Jared C	. Oatney		Collection Method			
RR#, Street Address, Box #: 10705 West -61 Hwv.					☐ GPS unit (Make/Model: Garmin csx			
City	, State, Z	IP Code : Partrido	e. Kansas 67566		Digital Map/I	hoto, Topographi	c Map, Land Survey	
Est. Accuracy: □ <3 m, □ 5-15 m, □ >15 m								
	A I E WE! H AN "X'		COMPLETED WELL	լ 45	fi	t.		
		ON BOX: Depth(s) Groundwater Encountered (1)						
	N WELL'S STATIC WATER LEVEL. 23ft. below land surface measured on mo/day/yr. 7-13-11							
	Pump test data: Well water wasft. after hours pumping gpm							
EST. YIELDgpm. Well water wasft. after hours pumpinggpm								
w								
1 1	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SV	SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes V No								
S If yes, mo/day/yr sample was submitted								
Water well disinfected? ✓ Yes No								
5 TYPE OF CASING USED: Steel V PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter 16 in to 33 ft., Diameter in to ft., Diameter in to ft.								
Casing height above land surface. 24 in., Weight SCH 40 lbs./ft., Wall thickness or gauge No500								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From33 ft. to45 ft., From ft. to ft.								
From								
GRAVEL PACK INTERVALS: From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From 17 ft. to 0 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)								
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well .none								
		n well				gas wen		
FROM	TO	LITHOLOG		FROM			GGING INTERVALS	
0	3	Top soil				, , , , , , , , , , , , , , , , , , , ,		
3	6	Tan sandy clay						
6	15	Medium to fine sand						
15	18	Tan clay						
18	44	Medium to small sand						
44	45	Red bed		 				
	,							
				 				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .7-13-11								
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 8-5-2011								
under the business name of Rosencrantz-Bernis Ent. by (signature) Livera Dates								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy								

47,301