

1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 SW 1/4 Section Number 27 Township Number T 25 S Range Number R 1 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: Terry & Karen Fillenworth
 RR#, St. Address, Box #: 6900 Glenda
 City, State, ZIP Code: Valley Center, KS 67147
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
	NW	NE	
W			E
	SW	SE	
			S

1 Mile

4 DEPTH OF COMPLETED WELL: 45 ft. ELEVATION: 5/20/96
 Depth(s) Groundwater Encountered 1. 20 ft. 2. 45 ft. 3. 45 ft.
 WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 5/20/96
 Pump test data: Well water was 20 ft. after 11 hours pumping 45 gpm
 Est. Yield 20 gpm Well water was 45 ft. after 11 hours pumping 45 gpm
 Bore Hole Diameter 11 in. to 45 ft. and 45 in. to 45 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
☒ 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
☒ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded X
 Blank casing diameter 12 in. to 38 ft. Dia. 2.60 in. to 160 ft. Dia. 160 PSI
 Casing height above land surface 12 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 160
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) X
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 45 10 Other (specify) 45
 SCREEN-PERFORATED INTERVALS: From 38 ft. to 45 ft. From 45 ft. to 45 ft.
 From 19 ft. to 45 ft. From 45 ft. to 45 ft.
 GRAVEL PACK INTERVALS: From 19 ft. to 45 ft. From 45 ft. to 45 ft.

6 GROUT MATERIAL: 1 Neat cement 3 Bentonite 4 Other 150
 Grout Intervals: From 3 ft. to 19 ft. From 19 ft. to 45 ft. From 45 ft. to 45 ft.
 What is the nearest source of possible contamination: Septic tank 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 4 Lateral lines 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 5 Cess pool 12 Fertilizer storage 16 Other (specify below)
 6 Seepage pit 8 Sewage lagoon 13 Insecticide storage
 Direction from well? East How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	15	clay			
15	30	fine sand			
30	45	gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/20/96 and this record is true to the best of my knowledge and belief. Kansas Water Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6/28/96
 under the business name of Weminger Drilling, Inc by (signature)