

1 LOCATION OF WATER WELL: County: Sedgewick Fraction SW 1/4 SE 1/4 NW 1/4 Section Number 36 Township Number 25 Range Number 1 E

Distance and direction from nearest town or city street address of well if located within city? S 20 Deerfield C.R. Valley Center KS

2 WATER WELL OWNER: Jim Breitenbach RR#, St. Address, Box #: 520 Deerfield C.R. City, State, ZIP Code: Valley Center KS 67147 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SW section of the 4th township, 36th range, 1st E]

4 DEPTH OF COMPLETED WELL: 47 ft. ELEVATION: 41 ft. Depth(s) Groundwater Encountered: 1. 18 ft. 2. 41 ft. 3. WELL'S STATIC WATER LEVEL: UN ft. below land surface measured on mo/day/yr Pump test data: Well water was UN ft. after UN hours pumping UN gpm Est. Yield: UN gpm Well water was UN ft. after UN hours pumping UN gpm Bore Hole Diameter: 10 in. to 8 1/4 in. to UN in. to UN in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter: 5 in. to 41 in. Dia. 14 in. weight lbs./ft. Wall thickness or gauge No. 25 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 41 ft. From GRAVEL PACK INTERVALS: From 25 ft. to 41 ft. From

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 25 ft. From What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage How many feet? 80+

Direction from well? South

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	14	Clay			
14	21	Fine sand			
21	26	Clay			
26	41	Med gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-31-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 611 This Water Well Record was completed on (mo/day/yr) 12-31-96 under the business name of Chase Drilling by (signature) Phil Chase

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.