

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SW 1/4 SW 1/4 NW 1/4		7		T 25 S		R 1 E/W	
Distance and direction from nearest town or city street address of well if located within city?									
Approximately 2 miles east and 1/2 mile north of Bentley									
2 WATER WELL OWNER: City of Wichita									
RR#, St. Address, Box #: 455 N. Main									
City, State, ZIP Code: Wichita, KS 67202									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:									
4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: unknown									
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.									
WELL'S STATIC WATER LEVEL: 31.10 ft. below land surface measured on mo/day/yr 5-15-97									
Pump test data: Well water was not ch'd. ft. after hours pumping gpm									
Est. Yield unknown gpm: Well water was ft. after hours pumping gpm									
Bore Hole Diameter: 6 in. to 34.5 ft., and in. to ft.									
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No X									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded									
2 PVC 4 ABS 7 Fiberglass Threaded									
Blank casing diameter 2 in. to 24 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 24 in., weight 7.0 lbs./ft. Wall thickness or gauge No. 154									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 24 ft. to 34 ft., From ft. to ft.									
From ft. to ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 22 ft. to 34 ft., From ft. to ft.									
From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug									
Grout Intervals: From ft. to ft., From ft. to ft., From 0 ft. to 22 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage None known									
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 3 Topsoil									
3 7 Clay, brown, hard									
7 34 Sand and gravel, coarse, medium, fine									
34 34.5 Clay, black, soft									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-15-97 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 5-30-97									
under the business name of Clarke Well & Equipment, Inc. by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									

WELL RECORD

DESIGN & CONSTRUCTION SHEET



FORMATION LOG. From test no.			Formation Thickness	From ground level	From	To	Ftg.
from	to						
0	3	Topsoil		Casing	0	24	24
3	7	Clay, brown, hard		Screen	24	34	10
7	34	Sand and gravel, coarse, medium,					
		fine					
34	34.5	Clay, black, soft					
				CASING LEFT ABOVE GROUND			2
				TOTAL CASING & SCREEN			36

GRAVEL PACK	ANNULAR SEAL	
22 TO 34	0 TO 22	Bentonite Holeplug
TO	TO	

DIRECTION FROM WELL	HOW MANY FEET
---------------------	---------------

DESIGNED BY _____ DRILLED BY Edward Cass DATE 5-15-97