

1 LOCATION OF WATER WELL: County: Sedgwick SW 1/4 SW 1/4 SW 1/4 Section Number 20 Township Number 25S Range Number 1E Distance and direction from nearest town or city street address of well if located within city? 10240 W. 93rd N.

2 WATER WELL OWNER: Bob Hirschler RR#, St. Address, Box #: 7901 N. Marz Rd. City, State, ZIP Code: Wichita, KS 67147 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with the well located in the SW corner of the NW section, marked with an 'X']

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 1-23-98 ft. below land surface measured on mo/day/yr

WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 20 gpm ft. after 11 in. to 60 ft. and 1600 PSI

Est. Yield: 20 gpm Well water was 11 in. to 60 ft. and 1600 PSI

Bore Hole Diameter: 11 in. to 60 ft. and 1600 PSI

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded

Blank casing diameter: 5 in. to 50 ft. Dia 2.40 in. to 1600 PSI

Casing height above land surface: 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 1600 PSI

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft. From 16 ft. to 60 ft.

GRAVEL PACK INTERVALS: From 16 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 16 ft. From 16 ft. to 60 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage open field

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	31	fine to medium sand			
31	38	clay			
38	60	sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-23-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 1-23-98 under the business name of Weninger Drilling Inc. by (signature) Michele Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.