

1 LOCATION OF WATER WELL:		Fraction	Township Number		Range Number
County: SEDGWICK		SW 1/4 NW 1/4 SE 1/4	36		T 25 S R 1 E
Distance and direction from nearest town or city street address of well if located within city?					
1000' SW OF VALLEY CENTER, KS			WELL 11/25		
2 WATER WELL OWNER:		BARTON SOLVENTS		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box # :		201 SOUTH CEDAR		Application Number:	
City, State, ZIP Code :		VALLEY, KS 67147			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 32.5 ft. ELEVATION: 1347			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 2 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 32.5 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well SPARGE POINT			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below)		Welded	
2 PVC 4 ABS		7 Fiberglass		Threaded FLUSH	
Blank casing diameter 2.375 in. to 30.0 ft. Dia		in. to ft. Dia		in. to ft. Dia	
Casing height above land surface 0 in., weight 0.687 lbs./ft.		Wall thickness or gauge No. SCH 40 (0.154)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		67 PVC		10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)		12 None used (open hole)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		7 Torch cut 10 Other (specify)			
2 Louvered shutter 4 Key punched					
SCREEN-PERFORATED INTERVALS: From 30.0 ft. to 32.5 ft.		From ft. to ft.		From ft. to ft.	
GRAVEL PACK INTERVALS: From 29.5 ft. to 32.5 ft.		From ft. to ft.		From ft. to ft.	
6 GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other BENTONITE 29 TO 29.5					
Grout Intervals: From 0 ft. to 29.0 ft.		From ft. to ft.		From ft. to ft.	
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	TOP SOIL			
1	14	BROWN CLAY			
14	32.5	VERY FINE TO FINE SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 581 This Water Well Record was completed on (mo/day/yr) 11/1/00 under the business name of CAYNE WESTERN, A DIV OF LAYNE CHRISTENSEN by (signature) Kayne West					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					