

1 LOCATION OF WATER WELL: County: Sedgewick NW 1/4 NE 1/4 NE 1/4 Section Number 19 30 Township Number 25S Range Number 1E Distance and direction from nearest town or city, street address of well if located within city? 101st N & 103rd W - Southwest track 1 block 2 Bentley Farms

2 WATER WELL OWNER: James Roach RR#, St. Address, Box #: 5733 N. St. Clair City, State, ZIP Code: Wichita, KS 67204 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NE section of the top-left 4-section block]

4 DEPTH OF COMPLETED WELL: 51 ft. ELEVATION: 1020-00 ft. WELL'S STATIC WATER LEVEL: 25 ft. below land surface measured on mo/day/yr Pump test data: Well water was 25 ft. after 10 hours pumping 25 gpm Est. Yield 25 gpm Well water was 51 ft. after 10 hours pumping 25 gpm Bore Hole Diameter: 11 in. to 51 in. and 51 in. to 51 in. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 12 in. to 43 in. Dia 2.40 in. to 160 psi Casing height above land surface 2.40 in. weight lbs./ft. Wall thickness or gauge No. 160 psi TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 43 ft. to 51 ft. From 25 ft. to 51 ft. GRAVEL PACK INTERVALS: From 25 ft. to 51 ft. From 25 ft. to 51 ft.

6 GROUT MATERIAL: 3 1 Neat cement 25 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 25 ft. From 25 ft. to 51 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage How many feet? 60 Direction from well? East

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-20-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-20-00 under the business name of Wenginger Drilling Inc. by (signature) Michael Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.