

1 LOCATION OF WATER WELL: WATER WELL RECORD Form WWR-3 RCR 028-1212 10 NO. Section Number Township Number Range Number

County: Sedgwick SE 1/4 NE 1/4 SE 1/4 36 T 25 S R 1 EW

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: USD # 362 Bus Garage

RR#, St. Address, Box #: 2155 S. Park

City, State, ZIP Code: Valley Center, KS

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL: 20' ft. ELEVATION:

AN "X" IN SECTION BOX:

Depth(s) Groundwater Encountered: 13' ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 14.74 ft. below land surface measured on mo/day/yr 11-15-00

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 8 1/2 in. to 20' ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. Clamped.

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

7 Fiberglass Threaded X

Blank casing diameter: 2.375 in. to 10' ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface: Flush ft. in., weight lbs./ft. Wall thickness or gauge No. SDR-13

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement Sch 40

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 20' ft. to 9' ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 4' ft. to 4' ft. From 4' ft. to 0' ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage Fueler 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? West S. West How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 1.75 Asphalt

1.75 5.0 DK-Med. Bn. clay w/trace sand of caliche dry, no odor

5.0 8.0 Bn. silt, dry

8.0 11.20 Bn. clay w/trace caliche

11.20 13.0 Bn. clay, silt, moist, no odor

13.0 20.0 Bn. fine - coarse sand & gravel wet at 13', no odor

F.M. OK'd by D. Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-14-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 539 This Water Well Record was completed on (mo/day/yr) 11-16-00 under the business name of QB Env. Drilling by (signature) James Becker

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.