

1 LOCATION OF WATER WELL: Fraction NW NE 1/4 NE 1/4 Section Number 19 30 Township Number T 25 S Range Number R 1 E 10
County: Sedgwick Distance and direction from nearest town or city street address of well if located within city? 1012 NE 103rd W southwest track 3 block 3

2 WATER WELL OWNER: James Roach
RR#, St. Address, Box #: 5733 N. St. Clair
City, State, ZIP Code: Wichita, KS 67204
Board of Agriculture, Division of Water Resources
Application Number: Bentley Farms

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION: 55 ft.
 Depth(s) Groundwater Encountered: 1. 25 ft. 2. 55 ft. 3. 10-27-01 ft.
 WELL'S STATIC WATER LEVEL: 25 ft. below land surface measured on mo/day/yr 10-27-01
 Pump test data: Well water was 25 ft. after 11 hours pumping 55 gpm
 Est. Yield: 25 gpm Well water was 11 ft. after 55 hours pumping 55 gpm
 Bore Hole Diameter: 11 in. to 55 ft. and 55 in. to 55 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 12 30 in. to 2.40 ft. Dia. 160 PSI
 Casing height above land surface: 2.40 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160 PSI
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 55 ft. From 25 ft. to 55 ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 55 ft. From 25 ft. to 55 ft.

6 GROUT MATERIAL: 3 1 Neat cement 25 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 25 ft. From 25 ft. to 55 ft. From 55 ft. to 60 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Southwest How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	16	clay			
16	30	fine sand			
30	55	med. sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-27-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-27-01 under the business name of Weninger Drilling Inc. by (signature) Michael Gorg

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4