

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 Section Number 19 Township Number 25S Range Number 1E
County Sedgwick Distance and direction from nearest town or city street address of well if located within city?
YORSEN E 103rd N - Southwest - Bentley Farms lot 1 Block 1

2 WATER WELL OWNER: James Roach
RR#, St. Address, Box #: 5733 N. St. Clair
City, State, ZIP Code: Wichita, KS 67204
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
1 Mile
W E
N S
X

4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 7-23-01
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield 25 gpm Well water was ft. after hours pumping gpm
Bore Hole Diameter 11 in. to 65 ft. and in. to ft.
WELL WATER TO BE USED AS:
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter 5 in. to 51 ft. Dia in. to ft. Dia in. to ft.
Casing height above land surface 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160psi
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 51 ft. to 65 ft. From ft. to ft.
From 15 ft. to 65 ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 15 ft. to 65 ft. From ft. to ft.
From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 3 Neat cement 15 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 15 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? How many feet?

LITHOLOGIC LOG
FROM TO
0 2 top soil
2 16 clay
16 25 sand
25 35 clay
35 65 med. sand

PLUGGING INTERVALS
FROM TO
0 2
2 16
16 25
25 35
35 65

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-23-01 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-27-01
under the business name of WENINGER DRILLING INC. by (signature) Michael George

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.