

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>SW 1/4 SW 1/4 NW 1/4</u>	<u>35</u>	<u>(25) 29 S</u>	<u>R 1 EW</u>
Distance and direction from nearest town or city street address of well if located within city: <u>8160 N. Hoover</u>					
2 WATER WELL OWNER: <u>Lamyouphant</u>					
RR#, St. Address, Box #: <u>1400 Sunnyside</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: <u>Valley Center KS 67147</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>36</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>18</u> ft. below land surface measured on mo/day/yr <u>10-11-01</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <u>25</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>11</u> in. to <u>36</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)			
		☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☒ No ☒			
5 TYPE OF BLANK CASING USED:					
☒ 1 Steel ☐ 3 RMP (SR) ☐ 2 PVC ☐ 4 ABS		☐ 5 Wrought iron ☐ 6 Asbestos-Cement ☐ 7 Fiberglass		☐ 8 Concrete tile ☐ 9 Other (specify below) CASING JOINTS: Glued ☒ Clamped ☒ Welded Threaded	
Blank casing diameter <u>5</u> in. to <u>26</u> ft., Dia		Casing height above land surface <u>12</u> in., weight <u>240</u> lbs./ft. Wall thickness or gauge No. <u>160psi</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS		☒ 7 PVC ☐ 10 Asbestos-cement ☐ 8 RMP (SR) ☐ 11 Other (specify) ☐ 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 2 Louvered shutter ☐ 4 Key punched		☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 7 Torch cut ☐ 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From <u>26</u> ft. to <u>36</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>18</u> ft. to <u>36</u> ft., From ft. to ft.					
6 GROUT MATERIAL: ☒ 1 Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>18</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard		☐ 10 Livestock pens ☐ 14 Abandoned water well ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐ 13 Insecticide storage			
Direction from well? <u>southeast</u>		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>2</u>	<u>top soil</u>			
<u>2</u>	<u>36</u>	<u>fine to med. sand</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-11-01</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>10-15-01</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Michael George</u>					