

1 LOCATION OF WATER WELL: Fraction NE 1/4 SW 1/4 NE 1/4 Section Number 3019 Township Number 25 S Range Number 1 E

County: Sedgewick Distance and direction from nearest town or city street address of well if located within city? 10 1/2 N E 10 3/4 W - SW "Butterfarms" block 3 lot 5

2 WATER WELL OWNER: James Roach RR#, St. Address, Box #: 5733 N. St. Clair City, State, ZIP Code: Wichita, KS 67204-36

Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-acre section with an 'X' in the NE corner]

4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 6-4-02

Depth(s) Groundwater Encountered: 10 ft. below land surface measured on mo/day/yr

WELL'S STATIC WATER LEVEL: 10 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 25 gpm: Well water was 11 in. to 36 ft., and 36 ft. to 100 psi

Est. Yield: 25 gpm: Well water was 11 in. to 36 ft., and 36 ft. to 100 psi

Bore Hole Diameter: 11 in. to 36 ft., and 36 ft. to 100 psi

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 5 4 ABS 7 Fiberglass

Casing diameter: 12 in. to 26 ft., Dia 2.40 in. to 100 psi

Casing height above land surface: 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 100 psi

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft. From 36 ft. to 100 psi

GRAVEL PACK INTERVALS: From 10 ft. to 36 ft. From 36 ft. to 100 psi

6 GROUT MATERIAL: 3 Neat cement 100 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 100 ft. From 100 ft. to 100 ft. From 100 ft. to 100 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	8	clay			
8	36	fine to med sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-4-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 6-4-02 under the business name of Waininger Drilling Inc. by (signature) Rickie George

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.