

1 LOCATION OF WATER WELL: Fraction		Section Number		Township Number		Range Number	
County: Sedgwick NE 1/4 SE 1/4 SE 1/4		36		T 25S S		R 14W E/W	
Distance and direction from nearest town or city street address of well if located within city? 800 N. Meridian; Valley Center							
2 WATER WELL OWNER: Valley Center High School							
RR#, St. Address, Box # : 800 N. Meridian				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Valley Center, KS				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 9 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 9 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:							
1 Steel 2 PVC		3 RMP (SR) 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass		8 Concrete tile 9 Other (specify below)	
CASING JOINTS: Glued X Clamped Welded Threaded							
Blank casing diameter 6 in. to 60 ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface 16 in. weight 160 lbs./ft. Wall thickness or gauge No. 26							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 2 Brass		3 Stainless Steel 4 Galvanized Steel		5 Fiberglass 6 Concrete tile		7 PVC 8 RMP (SR) 9 ABS	
10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 2 Louvered shutter		3 Mill slot 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut		8 Saw cut 9 Drilled holes 10 Other (specify)	
11 None (open hole) ft.							
SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 24 ft. to 60 ft. From ft. to ft.							
From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL:							
1 Neat cement 2 Cement grout		3 Bentonite		4 Other			
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 2 Sewer lines 3 Watertight sewer lines		4 Lateral lines 5 Cess pool 6 Seepage pit		7 Pit privy 8 Sewage lagoon 9 Feedyard		10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	
14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)							
Direction from well? NONE How many feet?							
FROM TO		LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS	
0 2		topsoil					
2 17		brown clay					
17 41		med coarse sand					
41 43		brown clay					
43 56		med coarse sand gravel					
56 60		blue shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-29-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 611 This Water Well Record was completed on (mo/day/yr) 2-4-05 under the business name of Chase Drilling by (signature) E. Chase							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.							