


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NW 1/4 SW 1/4 SW 1/4	Section Number 27	Township Number T 25 S	Range Number R 1 W 11 E/W
Distance and direction from nearest town or city street address of well if located within city? 8911 Ross Valley Center, Kansas					
2 WATER WELL OWNER: Floyd Bliss RR#, St. Address, Box # : 2325 Payne City, State, ZIP Code : Wichita, Ks. Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 17 ft.			
		Depth(s) Groundwater Encountered 1. 17 ft. 2. 17 ft. 3. 17 ft.			
		WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 8-22-83			
		Pump test data: Well water was 11 ft. after 11 hours pumping 11 gpm			
		Est. Yield 11 gpm: Well water was 11 ft. after 11 hours pumping 11 gpm			
Bore Hole Diameter 11 in. to 11 in. and 11 in. to 11 in.		WELL WATER TO BE USED AS:			
1 Domestic 11		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 11		3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
4 Industrial 7 Lawn and garden only 10 Observation well		Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped X			
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded X			
2 PVC 4 ABS		7 Fiberglass Cer-Mac styrene SDR-26 Threaded X			
Blank casing diameter 5 in. to 35 in. Dia 5 in. to 35 in. Dia 5 in. to 35 in.		Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. 203			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 8 Saw cut		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 7 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 8 Saw cut			
SCREEN-PERFORATED INTERVALS: From 35 ft. to 50 ft. From 35 ft. to 50 ft.		GRAVEL PACK INTERVALS: From 14 ft. to 50 ft. From 14 ft. to 50 ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 4 ft. to 14 ft. From 4 ft. to 14 ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage NONE APPARENT		Direction from well? How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	16	Clay			
16	27	Fine Sand			
27	50	Medium Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-22-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 . This Water Well Record was completed on (mo/day/yr) 12-30-83 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					