


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE 1/4 SE 1/4 NE 1/4	15	T 25 S	R 1 W E/W
Distance and direction from nearest town or city street address of well if located within city? Ridge Rd. to Bentley Rd., 1/2 E., 1/2 S., W. side, Valley Center, Ks.					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		Valley Center, Ks.			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 53 ft. ELEVATION: 16 ft.			
		Depth(s) Groundwater Encountered 1. 16 ft. 2. . ft. 3. . ft.			
		WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 1-14-82			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm			
Bore Hole Diameter . 11 in. to . ft., and . in. to . ft.		WELL WATER TO BE USED AS:			
5 Public water supply		8 Air conditioning		11 Injection well	
1 Domestic		3 Feedlot		6 Oil field water supply	
2 Irrigation		4 Industrial		9 Dewatering	
7 Lawn and garden only		10 Observation well		12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes. . No. X. ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued . X . Clamped .			
1 Steel		3 RMP (SR)		Welded .	
2 PVC		4 ABS		Threaded .	
Blank casing diameter . 5 in. to . 33 ft. Dia . in. to . ft. Dia . in. to . ft.		Cer-Mac Styrene SDR-26 lbs./ft. Wall thickness or gauge No. . 203			
Casing height above land surface . 12 in. weight . 1.59					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC			
1 Steel		3 Stainless steel		10 Asbestos-cement	
2 Brass		4 Galvanized steel		11 Other (specify) .	
5 Fiberglass		8 RMP (SR)		12 None used (open hole)	
6 Concrete tile		9 ABS			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped			
1 Continuous slot		3 Mill slot		8 Saw cut	
2 Louvered shutter		4 Key punched		9 Drilled holes	
5 Wire wrapped		7 Torch cut		10 Other (specify) .	
SCREEN-PERFORATED INTERVALS:		From . 33 ft. to . 53 ft. From . ft. to . ft.			
GRAVEL PACK INTERVALS:		From . 14 ft. to . 53 ft. From . ft. to . ft.			
6 GROUT MATERIAL:		4 Other .			
1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From . 4 ft. to . 14 ft. From . ft. to . ft. From . ft. to . ft.					
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		4 Lateral lines		14 Abandoned water well	
2 Sewer lines		5 Cess pool		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		12 Fertilizer storage	
7 Pit privy		8 Sewage lagoon		15 Oil well/Gas well	
9 Feedyard		13 Insecticide storage		16 Other (specify below)	
Direction from well? North		How many feet? 67			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	11	Clay			
11	39	Fine Sand			
39	53	Medium Sand and Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-14-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 3-5-82 under the business name of Harp Well & Pump Serv., Inc. by (signature) M. Arnold					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC 15

SE

1/4

SE

1/4

NE

1/4