

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Sedgwick	Fraction SW 1/4 SW 1/4 SE 1/4	Section number 22	Township number T 25 S R 1	Range number EW				
2. Distance and direction from nearest town or city: 3 W Valley Center 1 N 1/2 E			3. Owner of well: Bill Wilbur R.R. or street: R.R.1, City, state, zip code: Valley Center, Kans. 67135							
4. Locate with "X" in section below: N 1 Mile W <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td>NW</td><td>NE</td></tr><tr><td>SW</td><td>SE</td></tr></table> E S 1 Mile			NW	NE	SW	SE	Sketch map: 			
NW	NE									
SW	SE									
5. Type and color of material			From	To	6. Bore hole dia. 28 in. Completion date 9-22-79 Well depth 55 ft.					
Top Soil			0	3	7. Cable tool ☒ Rotary ☐ Driven ☐ Dug Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary					
Brown Clay			3	5	8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☒ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other					
Brown Clay			5	15	9. Casing: Material Transite Height: Above or below Threaded ☐ Welded ☐ Surface 12 in. RMP ☐ PVC ☐ Weight 30 lbs./ft. Dia. 16 in. to 0 ft. depth Wall Thickness: inches or Dia. 16 in. to 29 ft. depth gage No. 3/4					
Fine Sand With Clay			15	20	10. Screen: Manufacturer's name Johnson Type Sawed Dia. 16 Slot/gauze 3/16 Length 26 Set between 16.29 ft. and 29.55 ft. ft. and 1/4-1/8 ft. Gravel pack? yes Size range of material 1/4-1/8					
Fine Sand			20	25	11. Static water level: 16' ft. below land surface Date 9-22-79					
Medium Sand			25	35	12. Pumping level below land surfaces: 37 ft. after 1 hrs. pumping 500 g.p.m. 34 ft. after 1 hrs. pumping 400 g.p.m. Estimated maximum yield 500 g.p.m.					
Medium Sand With Very Little Clay			35	40	13. Water sample submitted: 16' mo./day/yr. ☐ Yes ☒ No Date 9-22-79					
Medium Sand			40	45	14. Well head completion: ☐ Pitless adapter 12 inches above grade					
Medium Fine Sand With Clay			45	53	15. Well grouted? yes With: ☐ Neat cement ☐ Bentonite ☒ Concrete Depth: From 0 ft. to 10 ft.					
Clay			53	55	16. Nearest source of possible contamination: ft. none Direction none Type none 17. Pump: ☒ Not installed Manufacturer's name Johnson Model number 1211 HP 1 Volts 115 Length of drop pipe 10 ft. capacity 500 g.p.m. Type: ☐ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other					
(Use a second sheet if needed)					20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Rosencrantz - Bemis Ent. Inc. 134 Business name 1211 W. 4th. Hutch. Kansa. License No. 1211 Address 1211 W. 4th. Hutch. Kansa. Signed Mike Jones Date 9-30-79 Authorized representative					
18. Elevation:		19. Remarks:								
Topography: ☐ Hill ☒ Slope ☐ Upland ☐ Valley										

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5