

1 LOCATION OF WATER WELL: County: Sedgwick Fraction: SW 1/4 NW 1/4 NW 1/4 Section Number: 22 Township Number: T 25 S Range Number: R 1 E
Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Robert Daniels
RR#, St. Address, Box #: 130 miles
City, State, ZIP Code: Valley Center KS 67147
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
N
W E
S
1 Mile
WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on 7-17-81
Pump test data: Well water was 21 ft. after 12 hours pumping 20 gpm
Est. Yield 50 gpm; Well water was 21 ft. after 12 hours pumping 20 gpm
Bore Hole Diameter: 11 in. to 61 ft., and 61 in. to 61 ft.
WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
1 Steel ☒ 3 RMP (SR) ☐ 4 ABS ☐ 5 Wrought iron ☐ 6 Asbestos-Cement ☐ 7 Fiberglass ☐ 8 Concrete tile ☐ 9 Other (specify below)
Blank casing diameter: 5 in. to 45 ft., Dia. 45 in. to 45 ft., Dia. 45 in. to 45 ft., Dia. 45 in. to 45 ft., Dia.
Casing height above land surface: 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SOR-26
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel ☐ 2 Brass ☐ 3 Stainless steel ☐ 4 Galvanized steel ☐ 5 Fiberglass ☐ 6 Concrete tile ☐ 7 PVC ☐ 8 RMP (SR) ☒ 9 ABS ☐ 10 Asbestos-cement ☐ 11 Other (specify) ☐ 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot ☐ 2 Louvered shutter ☐ 3 Mill slot ☒ 4 Key punched ☐ 5 Gauzed wrapped ☐ 6 Wire wrapped ☐ 7 Torch cut ☐ 8 Saw cut ☐ 10 Other (specify) ☐ 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 45 ft. to 61 ft., From 45 ft. to 61 ft., From 45 ft. to 61 ft., From 45 ft. to 61 ft.
GRAVEL PACK INTERVALS: From 13 ft. to 61 ft., From 13 ft. to 61 ft., From 13 ft. to 61 ft., From 13 ft. to 61 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other ☐
Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.
What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
13 Insecticide storage
Direction from well? North
How many feet? 125

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	17	Red clay			
17	25	fine sand			
25	26	Red clay			
26	40	med sand			
40	41	Red clay			
41	55	course gravel			
55	56	Red clay			
56	60	med sand			
60	61	green shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) 7-17-81 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-21-81
under the business name of Wenger Bros by (signature) Wenger Bros
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

END

SEC.

22

SW 1/4 NW 1/4 NW 1/4