

1	LOCATION OF WATER WELL: County: SEDGWICK	Fraction NE ¼ SE ¼ SW ¼	Section Number 27	Township Number T 25 S	Range Number R 1 W EW
---	---	----------------------------	----------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

NE corner of 85th North & Ridge Road, Valley Center, KS. Lot #22

2	WATER WELL OWNER:	Lawrence Adams	
	RR#, St. Address, Box # :	% George Clark	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	2551 Greenleaf	Wichita, Kansas
			Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL..... 35 ft. ELEVATION:

WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/vr 7-29-86

1 Mile
W

NW
--
SW

NE
--
SE

S
E

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter..... 11..... in. to ft., and..... in. to ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	11 Injection well
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Observation well	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes.....No **XX**.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes **XX** No

5	TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . XX . . . Clamped Welded Threaded
	1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	
	2 PVC	4 <u>ABS</u>	7 Fiberglass	Cer-Mac styrene SDR-26	

Blank casing diameter 5 . . . in. to 25 . . . ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 12 . . . in., weight 1.59 . . . lbs./ft. Wall thickness or gauge No. 203 . . .

TYPE OF SCREEN OR PERFORATION MATERIAL:			7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	<u>8 RMP (SR)</u>	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	<u>9 ABS</u>	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS:		From 25	ft. to 35	ft., From	ft. to	ft.
		From	ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:		From 14	ft. to 35	ft., From	ft. to	ft.
		From	ft. to	ft., From	ft. to	ft.

6	GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
	Grout Intervals:	From 4 ft. to 14 ft.	From 14 ft. to 14 ft.	From 14 ft. to 14 ft.	From 14 ft. to 14 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	<u>9 Feedyard</u>	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? West How many feet? 110

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-29-86. and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 12-3-86
under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.