

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County <u>Sedgwick</u>	Fraction <u>Center of</u> 1/4 1/4 NE 1/4	Section number <u>301</u>	Township number <u>25</u>	Range number <u>1</u> EW
2. Distance and direction from nearest town or city: Street address of well location if in city: <u>5 W. of Valley Center</u>			3. Owner of well: <u>Paul Seiler</u> R.R. or street: <u>Rt. 1</u> City, state, zip code: <u>Valley Center</u>		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. <u>30</u> in. Completion date <u>4-10-77</u> Well depth <u>147</u> ft.	
		<u>open field</u>		7. ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary	
				8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☒ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other	
5. Type and color of material		From	To	9. Casing: Material <u>C-Asb</u> Height: Above or below Threaded ☐ Welded ☐ Surface <u>12</u> in. RMP ☐ PVC ☐ Weight ☐ lbs./ft. Dia. <u>1 1/2</u> in. to <u>121</u> ft. depth Wall Thickness: inches or Dia. ☐ in. to ☐ ft. depth gage No. <u>7/4</u>	
<u>Topsoil</u>		<u>0</u>	<u>1</u>	10. Screen: Manufacturer's name <u>Johnson</u> Type <u>Cement-Asb</u> Dia. <u>16"</u> Slot gauge <u>1/4"</u> Length <u>36'</u> Set between <u>121</u> ft. and <u>147</u> ft. Gravel pack? ☒ Size range of material <u>3/8</u>	
<u>Fine Sand</u>		<u>1</u>	<u>15</u>	11. Static water level: <u>9</u> ft. below land surface Date <u>4-1-77</u>	
<u>Med Gravel</u>		<u>15</u>	<u>24</u>	12. Pumping level below land surfaces: <u>18</u> ft. after <u>2</u> hrs. pumping <u>900</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>1200</u> g.p.m.	
<u>Clay</u>		<u>24</u>	<u>32</u>	13. Water sample submitted: <u> </u> mo./day/yr. ☐ Yes ☒ No Date <u> </u>	
<u>Gravel</u>		<u>32</u>	<u>50</u>	14. Well head completion: ☐ Pitless adapter <u>12</u> Inches above grade	
<u>Clay</u>		<u>50</u>	<u>63</u>	15. Well grouted? ☒ With: ☐ Neat cement ☐ Bentonite ☒ Concrete Depth: From <u>0</u> ft. to <u>10</u> ft.	
<u>Gravel</u>		<u>63</u>	<u>75</u>	16. Nearest source of possible contamination: <u>none</u> ft. <u> </u> Direction <u> </u> Type <u> </u> Well disinfected upon completion? ☐ Yes ☒ No	
<u>Clay</u>		<u>78</u>	<u>86</u>	17. Pump: ☐ Not installed Manufacturer's name <u>Peerless</u> Model number <u>7261</u> HP <u>60</u> Volts <u> </u> Length of drop pipe <u>60</u> ft. capacity <u>900</u> g.p.m. Type: ☐ Submersible ☒ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
<u>Gravel</u>		<u>110</u>	<u>147</u>	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Weninger Irrigation</u> <u>238</u> Business name <u>Maize</u> License No. <u> </u> Address <u> </u> Signed <u>K. Weninger</u> Date <u>5-11-77</u> Authorized representative	
18. Elevation:		19. Remarks:			
Topography: ☐ Hill ☐ Slope ☒ Upland ☐ Valley					

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5