

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE ¼ SE ¼ NE ¼	32	T 25 S	R 1W EW
Distance and direction from nearest town or city street address of well if located within city?					
87th W. & 85th No. Wichita, Ks.					
2 WATER WELL OWNER:	George Clark				
RR#, St. Address, Box # :	2551 Greenleaf				
City, State, ZIP Code :	Wichita, Ks.				
					Board of Agriculture, Division of Water Resources Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 10-21-88				
	Depth(s) Groundwater Encountered 15 ft. 2. ft. 3. ft.				
	WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr				
	Pump test data: Well water was ft. after hours pumping gpm				
	Est. Yield gpm: Well water was ft. after hours pumping gpm				
	Bore Hole Diameter . 11 in. to ft., and in. to ft.				
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED:	CASING JOINTS: Glued <u>X</u> Clamped				
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded	
2 PVC	4 ABS	7 Fiberglass	Cer-Mac styrene SDR-26	Threaded	
Blank casing diameter 5 in. to 25 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes		
7 Torch cut	10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 23 ft. to 40 ft., From ft. to ft.					
FROM ft. to ft., FROM ft. to ft.					
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 3 ft. to 23 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
13 Insecticide storage					
Direction from well? North How many feet? 105					
FROM TO		LITHOLOGIC LOG	FROM TO		PLUGGING INTERVALS
0	3	topsoil			
3	7	sandy soil			
7	16	fine sand			
16	22	fine to coarse sand			
22	40	fine to coarse sand and gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-21-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 4-24-89 under the business name of Harp Well and Pump Service, Inc. by (signature) Mary Arnold					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					