

1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 NE 1/4 Section Number 35 Township Number T 25 S Range Number R 1 W
 County: Sedgwick Distance and direction from nearest town or city street address of well if located within city?
See Below

2 WATER WELL OWNER: CLAIR EVANS
 RR#, St. Address, Box #: 8201 N. West St
 City, State, ZIP Code: VALENTINE CENTER KS 67147 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	
E	SW	SE	
S			

4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: 21 ft. below land surface measured on mo/day/yr 1-10-91
 Depth(s) Groundwater Encountered 1. 21 ft. 2. 21 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr 1-10-91
 Pump test data: Well water was 21 ft. after 2 hours pumping 20 gpm
 Est. Yield 50 gpm: Well water was 21 ft. after 2 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 35 ft. and 35 in. to 35 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 15 ft. Dia. 15 in. to 35 ft. Dia. 35 in. to 35 ft. Dia.
 Casing height above land surface 12 in. weight 260 lbs./ft. Wall thickness or gauge No. 160 PVC
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 15 ft. to 35 ft. From 15 ft. to 35 ft.
 GRAVEL PACK INTERVALS: From 15 ft. to 35 ft. From 15 ft. to 35 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 15 ft. From 15 ft. to 35 ft. From 35 ft. to 35 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NE How many feet? 190

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top So.			
2	15	Clay			
15	35	Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-10-91 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 2-7-91
 under the business name of Weninger Drilling by (signature) [Signature]