

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range/Number
County: <u>Sedgwick</u>		<u>NW 1/4 NW 1/4 NE 1/4</u>	<u>35</u>	<u>T 25 S</u>	<u>R 1 E/W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1 1/2 miles West Valley Center</u>					
2 WATER WELL OWNER:					
RR#, St. Address, Box # : <u>Bill Gratton</u>					
City, State, ZIP Code : <u>Valley Center KS 67147</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>36</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>20</u> ft. 2. <u>36</u> ft. 3. <u>6-1-92</u> ft.			
		WELL'S STATIC WATER LEVEL <u>20</u> ft. below land surface measured on mo/day/yr <u>6-1-92</u>			
		Pump test data: Well water was <u>20</u> ft. after <u>36</u> hours pumping <u>gpm</u>			
		Est. Yield <u>gpm</u> Well water was <u>20</u> ft. after <u>36</u> hours pumping <u>gpm</u>			
Bore Hole Diameter <u>in.</u> to <u>ft.</u> and <u>in.</u> to <u>ft.</u>					
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>X</u> No <u>X</u>					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>X</u> 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> Blank casing diameter <u>5</u> in. to <u>27</u> ft. Dia. <u>2</u> in. to <u>160</u> lbs./ft. Wall thickness or gauge No. <u>160</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) <u>160</u> 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
SCREEN-PERFORATED INTERVALS: From <u>27</u> ft. to <u>36</u> ft. From <u>20</u> ft. to <u>36</u> ft.					
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>36</u> ft. From <u>20</u> ft. to <u>36</u> ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>100</u> Grout Intervals: From <u>3</u> ft. to <u>20</u> ft. From <u>20</u> ft. to <u>36</u> ft. From <u>20</u> ft. to <u>36</u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? <u>South</u> How many feet? <u>100</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	8	clay			
8	18	med sand			
18	21	clay			
21	36	med sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-1-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>316</u> This Water Well Record was completed on (mo/day/yr) <u>6-1-92</u> under the business name of <u>Weninger Drilling Inc</u> by (signature) <u>Susan K Weninger</u>					