

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County <u>Sedg.</u>	Fraction <u>SWSW NW</u>	Section number <u>36</u>	Township number <u>25</u>	Range number <u>1</u>
2. Distance and direction from nearest town or city: Street address of well location if in city: <u>1/2 W. Valley Center Ks.</u>				3. Owner of well: <u>MRS. Feland adst.</u> R.R. or street: <u>3734 W. 81st No.</u> City, state, zip code: <u>Valley Center Ks.</u>		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. <u>9 3/4</u> in. Completion date: <u>5/9/75</u> Well depth <u>45</u> ft.		
				7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
5. Type and color of material		From		To		8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other
<u>Top soil</u>		<u>0</u>		<u>8</u>		9. Casing: Material <u>Plast</u> Height: Above or below Threaded ☐ Welded ☒ Surface <u>18</u> in. RMP ☒ PVC ☐ Weight <u>2.82</u> lbs./ft. Dia. <u>5</u> in. to <u>45</u> ft. depth Wall thickness: inches or Dia. <u>5</u> in. to <u>45</u> ft. depth gage dia. <u>#200</u>
<u>Clay</u>		<u>8</u>		<u>18</u>		10. Screen: Manufacturer's name <u>JFL</u> Type <u>Plast</u> Dia. <u>5</u> in. Slot/auze <u>1/16</u> Length <u>10</u> ft. Set between <u>35</u> ft. and <u>45</u> ft. ft. and <u>45</u> ft. Gravel pack? <u>yes</u> Size range of material <u>3/8</u>
<u>fine to coarse gravel.</u>		<u>18</u>		<u>45</u>		11. Static water level: <u>18</u> ft. below land surface Date <u>5/9/75</u> mo./day/yr.
						12. Pumping level below land surfaces: ft. after <u>11</u> hrs. pumping <u>100</u> g.p.m. ft. after <u>11</u> hrs. pumping <u>100</u> g.p.m. Estimated maximum yield <u>100</u> g.p.m.
						13. Water sample submitted: <u>Yes</u> ☒ No ☐ Date <u>5/9/75</u> mo./day/yr.
						14. Well head completion: <u>18</u> Pitless adapter <u>18</u> inches above grade
						15. Well grouted? <u>yes</u> With: <u>Neat cement</u> ☐ Bentonite ☐ Concrete ☐ Depth: From <u>18</u> ft. to <u>45</u> ft.
						16. Nearest source of possible contamination: ft. <u>11</u> Direction <u>W</u> Type <u>W</u> Well disinfected upon completion? ☒ Yes ☐ No
						17. Pump: ☒ Not installed Manufacturer's name <u>Wenger</u> Model number <u>318</u> HP <u>3/4</u> Volts <u>115</u> Length of drop pipe <u>10</u> ft. capacity <u>100</u> g.p.m. Type: ☐ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Wenger Drilling</u> <u>318</u> Business name License No. Address <u>Colwich Ks</u> Signature <u>James Wenger</u> Date <u>5/9/75</u> Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5