

1 LOCATION OF WATER WELL: County: <u>Reno</u>	Fraction <u>SE 1/4 SE 1/4 NE 1/4</u>	Section Number <u>23</u>	Township Number T <u>25</u> S	Range Number R <u>10</u> E <u>W</u>
--	---	-----------------------------	----------------------------------	--

Distance and direction from nearest town or city street address of well if located within city?

From Langdon, KS - 1 mile North + 3 miles West

2 WATER WELL OWNER: <u>Larry Preisser</u> RR#, St. Address, Box # : <u>105 Southeast 130th Ave.</u> City, State, ZIP Code : <u>Sumner, KS 67035</u>	Board of Agriculture, Division of Water Resources Application Number: <u>45,908</u>
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>95</u> ft. ELEVATION: <u>4-15-06</u>
--	---

Depth(s) Groundwater Encountered 1 ft. 14 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 4-15-06

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 700 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
9 Dewatering	12 Other (Specify below)	
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)
10 Monitoring well		

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2</u> PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>16</u> in. to <u>55</u> ft., Dia			Threaded
Casing height above land surface <u>12</u> in., weight			lbs./ft. Wall thickness or guage No.
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <u>55</u> ft. to <u>95</u> ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From <u>20</u> ft. to <u>95</u> ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>3</u> ft. to <u>20</u> ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>None</u>
Direction from well?			How many feet?	<u>Open Field</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Sandy Soil			
2	17	Fine to coarse Sand			
17	30	Gray Clay			
30	36	Fine to coarse Sand			
36	50	to Fine Gravel			
36	50	Gray + Tan Clay			
50	70	W/ sand streaks			
70	74	Fine to coarse sand to Medium Gravel (same soil)			
74	95	Tan Clay			
		Fine to Medium to coarse Sand to Medium Gravel.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-15-06</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>238</u> This Water Well Record was completed on (mo/day/yr) <u>4-18-06</u> under the business name of <u>Premier Pump & Well Service Inc.</u> by (signature) <u>City of Warren</u>
