

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>	NW ¼ SE ¼ SW ¼	<u>34</u>	T <u>25</u> S	R <u>11</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

4 1/4 north, 2 east of Preston, Ks.

2 WATER WELL OWNER: <u>G.E. Geesling</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>33911 W. Sun City Rd.</u>	Application Number:
City, State, ZIP Code : <u>Turon, Ks. 67583</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>107</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>40</u> ft. below land surface measured on mo/day/yr <u>8-25-97</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>na</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>5 1/2</u> in. to <u>107</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Observation</u> Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>2 1/2</u> in. to <u>102</u> ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface <u>2'</u> in., weight <u>SDR 26</u> lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From <u>107</u> ft. to <u>102</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>107</u> ft. to <u>20</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>hole plug</u>
Grout Intervals: From <u>20</u> ft. to <u>0</u> ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? <u>west</u>	How many feet? <u>1000</u>			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Sandy top soil			
2	17	Brown clay			
17	34 1/2	Brown & white clay			
34 1/2	36	Fine sand			
36	41	Brown & white clay			
41	73	Sand and gravel clean, coarse, loose			
73	75	Clay w/ sand streaks			
75	80	Sand & gravel			
80	85	Yellow brown clay			
85	107	Sand and gravel medium loose			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-25-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>134</u> This Water Well Record was completed on (mo/day/yr) <u>9-5-97</u> under the business name of <u>Rosencrantz-breis</u> by (signature) <u>Media Redden</u>
--