

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Stafford		NW ¼ SE ¼ SE ¼	22	T 25 S	R 11 E/W

Distance and direction from nearest town or city street address of well if located within city?

Approxiamtely 3/4 mile south and 1/4 mile west of Neola

2 WATER WELL OWNER:		Max Nichols	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :		Box 515	Application Number:
City, State, ZIP Code :		Great Bend, KS 67530	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 134 ft. ELEVATION: unknown	
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.	
		WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 7-3-97	
		Pump test data: Well water was not ch'd. ft. after hours pumping gpm	
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm	
Bore Hole Diameter 6 in. to 133 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No <u>X</u>	

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 <u>PVC</u>	4 ABS	7 Fiberglass		Threaded
Blank casing diameter 2 1/2 in. to 127 ft. Dia		in. to ft. Dia in. to ft.		
Casing height above land surface 24 in. weight 63 lbs./ft.		Wall thickness or gauge No. 110		
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 <u>PVC</u>	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 <u>Drilled holes</u>	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 127 ft. to 132 ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:		From 122 ft. to 133 ft.	From ft. to ft.	

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>Bentonite Holeplug</u>
Grout Intervals: From ft. to ft.		From 0 ft. to 122 ft.			
What is the nearest source of possible contamination:					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
			13 Insecticide storage	None known	
Direction from well?		How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	16	Clay, brown			
16	24	Sand, fine, silty			
24	28	Clay, brown			
28	48	Sand and gravel, medium			
48	51	Clay, brown			
51	68	Sand and gravel, fine, medium			
68	76	Clay, brown			
76	103	Sand and gravel, medium, coarse			
103	105	Clay, gray			
105	132	Sand and gravel, fine, medium			
132	133	Clay, gray, hard			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-3-97 and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. 185	This Water Well Record was completed on (mo/day/yr) 7-24-97
under the business name of Clarke Well & Equipment, Inc.	by (signature)