

1 LOCATION OF WATER WELL:		Fraction		Form WWC-5		KSA 82a-1212			
County: STAFFORD		SW 1/4 NW 1/4 SE 1/4		Section Number 33		Township Number T 25 S		Range Number R 11 E/W	
Distance and direction from nearest town or city street address of well if located within city? 3-S 1-M OF NEOLA, KS.									
2 WATER WELL OWNER: DEUTSCH OIL CO.									
RR#, St. Address, Box #: 107 N. MARKET 1115 BITTING BLDG.						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: WICHITA, KS. 67202						Application Number: 93-0092			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 96 ft. ELEVATION:						
1 Mile W NW NE SW SE X E S			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 5 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot XX Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No						
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
XX PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 5 in. to 86 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL: XX PVC 10 Asbestos-cement									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot XX Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
3 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 86 ft. to 96 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 28 ft. to 96 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout XX Bentonite 4 Other									
Grout intervals: From 0 ft. to 20 ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage NONE									
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 3 TOP SOIL									
3 35 CLAY									
35 76 CLAY & SAND STREAKS									
76 96 GRAVEL									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was XX constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-28-93 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 462-8 This Water Well Record was completed on (mo/day/yr) 4-2-93									
under the business name of SAM'S WATER WELL SERVICE by (signature)									