


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Stafford		SE 1/4 NW 1/4 SE 1/4	10	T 25 25 S	R 12 W E/W
Distance and direction from nearest town or city street address of well if located within city? 4 miles south 1 west 3/4 south of Stafford					
2 WATER WELL OWNER: Brad Johnson		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : RR1 box 133		Application Number:			
City, State, ZIP Code : Stafford, Ks. 67578					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 49 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 32 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 16 1/2 ft. below land surface measured on mo/day/yr 10-26-99			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 15 gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 9 in. to ft. and 49 in. to ft.					
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: <u>Glued</u> <u>Clamped</u>			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		<u>Welded</u>			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		<u>Threaded</u>			
7 Fiberglass					
Blank casing diameter 5 in. to 39 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. 250					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 39 ft. to 49 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 23 ft. to 49 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 23 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? South		How many feet? 75			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	soil			
3	10	clay			
10	16	clay			
16	32	fine sand			
32	42	med sand			
42	44	fine sand			
44	48	good sand			
48	49	clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-26-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 140 This Water Well Record was completed on (mo/day/yr) 10-26-99 under the business name of Lyman Inc. by (signature) <i>Lyman Inc.</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4