

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Stafford		$\frac{1}{4}$ NC $\frac{1}{4}$ SW $\frac{1}{4}$	5	T 25 S	R 12 E/W
Distance and direction from nearest town or city street address of well if located within city? Approximately 4 miles south and 3 3/4 miles west of Stafford					
2 WATER WELL OWNER:		Don Fritzemeier			
RR#, St. Address, Box # :		Route 1 - Box 100			
City, State, ZIP Code :		Stafford, KS 67578			
		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION: unknown			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 21.85 ft. below land surface measured on mo/day/yr 4-9-98			
		Pump test data: Well water was not ch'd ft. after hours pumping gpm			
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 6 3/4 in. to 140 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Observation			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☒ Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 3 in. to 131 ft., Dia. 3 in. to 137 ft., Dia. in. to ft.		7 Fiberglass			
Casing height above land surface 36 in., weight 1.96 lbs./ft. Wall thickness or gauge No. 300		Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 131 ft. to 136 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 120 ft. to 140 ft., From ft. to ft.					
6 GROUT MATERIAL:		4 Other Bentonite Holeplug			
Grout Intervals: From 0 ft. to 113 ft., From ft. to ft., From 113 ft. to 120 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None known					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Topsoil			
6	41	Clay, brown			
41	67	Sand and gravel, coarse, medium, fine			
67	98	Clay, brown			
98	105	Sand and gravel, medium, fine			
105	119	Clay, brown			
119	136	Sand and gravel, medium, fine			
136	140	Shale, red			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-9-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 4-16-98 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke W. Clarke</i>					