

1. Location of well:	County: <u>Stafford</u>	Fraction: <u>NW/SE/SW</u> 1/4 1/4 1/4	Section number: <u>1</u>	Township number: <u>T 25 S R 12 E</u>	Range number: <u>12</u>				
2. Distance and direction from nearest town or city: <u>3 3/4 S of Stafford</u> Street address of well location if in city: <u>601st St Rd. EAST</u>			3. Owner of well: <u>Virgil Rice</u> R.R. or street: City, state, zip code: <u>Stafford, Ks.</u>						
4. Locate with "X" in section below: N 1 Mile W <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td>NW</td><td>NE</td></tr><tr><td>SW</td><td>SE</td></tr></table> E S 1 Mile			NW	NE	SW	SE	Sketch map: X		
NW	NE								
SW	SE								
5. Type and color of material			From	To	6. Bore hole dia. <u>29</u> in. Completion date <u>5-20-76</u> Well depth <u>48</u> ft.				
<u>Top Soil</u>			<u>0</u>	<u>3</u>	7. Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary				
<u>Clay</u>			<u>3</u>	<u>24</u>	8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other				
<u>Good Sand little Clay</u>			<u>24</u>	<u>32</u>	9. Casing: Material <u>Steel</u> Height: <u>Above or below</u> Threaded ☐ Welded ☐ Surface <u>18</u> in. RMP ☐ PVC ☐ Weight <u>18</u> lbs./ft. Dia. <u>16</u> in. to <u>48</u> ft. depth Wall Thickness: inches or Dia. <u>16</u> in. to <u>48</u> ft. depth gage No. <u>7</u>				
<u>Good Clean Sand & Gravel</u>			<u>32</u>	<u>44</u>	10. Screen: Manufacturer's name <u>Doerrs</u> Type <u>Steel</u> Dia. <u>16</u> Slot/groove <u>3/16</u> Length <u>14</u> Set between <u>34</u> ft. and <u>48</u> ft. Gravel pack? ☒ Size range of material <u>1/2 3/4 3/8</u>				
<u>Clay</u>			<u>44</u>	<u>44 1/2</u>	11. Static water level: <u>13</u> ft. below land surface Date <u>4-15-76</u> mo./day/yr.				
<u>Good Sand</u>			<u>44 1/2</u>	<u>46</u>	12. Pumping level below land surfaces: <u>8</u> ft. after <u>1</u> hrs. pumping <u>400</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>500</u> g.p.m.				
<u>Clay</u>			<u>46</u>	<u>50</u>	13. Water sample submitted: <u>Yes</u> ☒ No ☐ Date <u>4-15-76</u> mo./day/yr.				
					14. Well head completion: <u> </u> Pitless adapter <u> </u> Inches above grade				
					15. Well grouted? <u> </u> With: <u> </u> Neat cement <u> </u> Bentonite <u> </u> Concrete ☒ Depth: From <u>0</u> ft. to <u>10</u> ft.				
					16. Nearest source of possible contamination: ft. <u>400</u> Direction <u>N</u> Type <u>SEPTIC</u> Well disinfected upon completion? <u> </u> Yes ☐ No ☐				
					17. Pump: <u>Not installed</u> Manufacturer's name <u>WLR</u> Model number <u>4CM/10</u> HP <u>20</u> Valves <u> </u> Length of drop pipe <u>40</u> ft. capacity <u>400</u> g.p.m. Type: ☐ Submersible ☒ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other				
(Use a second sheet if needed)									
18. Elevation:	19. Remarks:								
Topography: ☐ Hill ☐ Slope ☐ Upland ☐ Valley									
			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Rosenkrantz-Bemis</u> <u>134</u> Business name License No. Address <u>Great Bend, Ks.</u> Signed <u>Freddie Rosenkrantz</u> Date <u>8/3/76</u> Authorized representative						

25 120 1 NW SE SW 1/4 1/4 1/4