


HILDEBRAND #5 WATER WELL RECORD Form WWC-5 KSA 82a-1212					
1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: STAFFORD		C 1/4 SW 1/4 SW 1/4	24	T 25 S	R 12 EW
Distance and direction from nearest town or city street address of well if located within city? STAFFORD 6785 EASTSIDE					
2 WATER WELL OWNER: STERLING DRILLING CO.			HILDEBRAND BROS, STAFFORD		
RR#, St. Address, Box #: 608129			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: STERLING, KS 67579			Application Number: T84-738		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 24			
		Depth(s) Groundwater Encountered 1. 24 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 10' ft. below land surface measured on mo/day/yr 9-26-84			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7 7/8 in. to 6.5 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued X Clamped
2 PVC		4 ABS	7 Fiberglass		Welded
					Threaded
Blank casing diameter 5 in. to 4.5 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1/8					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 45 ft. to 65 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 35 ft. to 65 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: NONE					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	TOP SOIL			
4	18	CLAY			
18	22	SANDY CLAY			
22	65	GRAVEL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-26-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 10-3-84 under the business name of REISER WATER WELL SERVICE by (signature) Reiser					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					