

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>	<u>NC 1/4 N 1/2 NE 1/4</u>	<u>15</u>	<u>T 25 S</u>	<u>R 13 EW</u>

Distance and direction from nearest town or city street address of well if located within city?

7 3/4 S, 3/4 E of St. John

2 WATER WELL OWNER:	<u>Trans Pac Oil</u>	<u>SFWW2460</u>
RR#, St. Address, Box # :	<u>1 Main Place- Ste. 1000</u>	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	<u>Wichita, Ks. 67202</u>	Application Number: <u>20020202</u>

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>65</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered <u>1</u> ft. 2 <u> </u> ft. 3 <u> </u> ft. WELL'S STATIC WATER LEVEL <u>21</u> ft. below land surface measured on mo/day/yr <u>12-7-02</u> Pump test data: Well water was <u> </u> ft. after <u> </u> hours pumping <u> </u> gpm Est. Yield <u>N/A</u> gpm: Well water was <u> </u> ft. after <u> </u> hours pumping <u> </u> gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 <u>Oil field water supply</u> 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well <u> </u> Was a chemical/bacteriological sample submitted to Department? Yes <u> </u> No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u> </u> No <u>X</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped <u> </u>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) <u> </u>
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-Cement
Blank casing diameter <u>5</u> in. to <u>45</u> ft., Dia <u> </u> in. to <u> </u> ft., Dia <u> </u> in. to <u> </u> ft.			11 Other (Specify) <u> </u>
Casing height above land surface <u>24</u> in., weight <u>SDR-26</u> lbs./ft. Wall thickness or gauge No. <u> </u>			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	7 PVC	
1 Steel	3 Stainless Steel	8 RMP (SR)	
2 Brass	4 Galvanized Steel	9 ABS	
SCREEN OR PERFORATION OPENINGS ARE:	5 Guazed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify) <u> </u> ft.	
SCREEN-PERFORATED INTERVALS: From <u>65</u> ft. to <u>45</u> ft., From <u> </u> ft. to <u> </u> ft., From <u> </u> ft. to <u> </u> ft.			
GRAVEL PACK INTERVALS: From <u>65</u> ft. to <u>20</u> ft., From <u> </u> ft. to <u> </u> ft., From <u> </u> ft. to <u> </u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>hole plug</u>
Grout Intervals: From <u>20</u> ft. to <u>0</u> ft., From <u> </u> ft. to <u> </u> ft., From <u> </u> ft. to <u> </u> ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
Direction from well? <u>South</u>				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below) <u> </u>
				How many feet? <u>1300</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Sandy XX top soil			
3	11	Gray clay			
11	17	Sandy gray clay			
17	24	Gray clay with ash			
24	37	Sandy, gray clay & gravel mix			
37	58	Sand & gravel clean, med, loose			
58	64	Tan clay & gravel mix			
64	65	Tan clay/ gravel streaks			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12-7-02</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>134</u> This Water Well Record was completed on (mo/day/yr) <u>12-12-02</u> under the business name of <u>Rosencrantz- Bemis</u> by (signature) <u>Gora Alope</u>
--