

1 LOCATION OF WATER WELL:		Fraction		Section Number	Township Number	Range Number
County: STAFFORD		SE ¼ SW ¼ SW ¼		4	T 25 S	R 13 E
Distance and direction from nearest town or city street address of well if located within city? ST. JOHN 6 1/2 S 3/4 W NORTH SIDE						
2 WATER WELL OWNER: PAW DRILLING CO. INC.						
RR#, St. Address, Box #: 1010 UNION CENTER						
City, State, ZIP Code: WICHITA, KS 67202						
MRS. CORNWELL, ST. JOHN, KS. Board of Agriculture, Division of Water Resources Application Number: T84-607						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: 938.4 ft.				
		Depth(s) Groundwater Encountered 1. 35 ft. 2. .ft. 3. .ft.				
		WELL'S STATIC WATER LEVEL 21. ft. below land surface measured on mo/day/yr				
		Pump test data: Well water was .ft. after . hours pumping gpm				
		Est. Yield gpm: Well water was .ft. after . hours pumping gpm				
		Bore Hole Diameter: 7.78 in. to 7.5 .ft., and .in. to .ft.				
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well				
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:						
1 Steel		3 RMP (SR)		5 Wrought iron		CASING JOINTS: Glued X Clamped
2 PVC		4 ABS		6 Asbestos-Cement		Welded
Blank casing diameter 5 in. to 5.5 ft., Dia		7 Fiberglass		9 Other (specify below)		Threaded
Casing height above land surface 12 in., weight 2.65 lbs./ft.				Wall thickness or gauge No. 21.4		
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel		3 Stainless steel		5 Fiberglass		7 PVC
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)
						9 ABS
						10 Asbestos-cement
						11 Other (specify)
						12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1/8						
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes
				7 Torch cut		10 Other (specify)
						11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 55 ft. to 75 ft.						
From .ft. to .ft., From .ft. to .ft.						
GRAVEL PACK INTERVALS: From 45 ft. to 75 ft.						
From .ft. to .ft., From .ft. to .ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout intervals: From 0 ft. to 1.0 ft., From .ft. to .ft., From .ft. to .ft.						
What is the nearest source of possible contamination: NONE						
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage
						13 Insecticide storage
						14 Abandoned water well
						15 Oil well/Gas well
						16 Other (specify below)
Direction from well? How many feet?						
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	
0	3	SAND & SOIL				
3	30	SAND & CLAY				
30	45	FINE SAND				
45	75	GRAVEL				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-3-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 9-19-84 under the business name of REISER WATER WELL SERV. INC. by signature [Signature]						
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.						