

1 LOCATION OF WATER WELL: County: Stafford		Fraction SW 1/4 NW 1/4 SW 1/4	Section Number 5	Township Number T 25 S	Range Number R 13 EW
Distance and direction from nearest town or city street address of well if located within city? 5 1/2 S 2 W 3/4 S OF ST JOHN, KS					
2 WATER WELL OWNER: Eldon Bunker			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #: St. John 67576			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION:		
			Depth(s) Groundwater Encountered 1. 35 ft. 2. . ft. 3. . ft.		
			WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 11 Nov. 81		
			Pump test data: Well water was . ft. after . hours pumping . gpm		
			Est. Yield 80 gpm: Well water was . ft. after . hours pumping . gpm		
Bore Hole Diameter 10 in. to 75 ft., and . in. to . ft.			WELL WATER TO BE USED AS:		
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			5 Public water supply 8 Air conditioning 11 Injection well		
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes . No ☒ . If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped . ☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded . 7 Fiberglass Threaded .					
Blank casing diameter 5 in. to 55 ft., Dia . in. to . ft., Dia . in. to . ft.					
Casing height above land surface 12 in., weight . lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) . 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) .					
SCREEN-PERFORATED INTERVALS: From 55 ft. to 75 ft., From . ft. to . ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 75 ft., From . ft. to . ft.					
6 GROUT MATERIAL: ☒ Neat cement 2 Cement grout 3 Bentonite 4 Other .					
Grout Intervals: From 0 ft. to 10 ft., From . ft. to . ft., From . ft. to . ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) NONE 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	5	Sand, very fine to fine			
5	35	Clay, tan and brown			
35	40	Sand, fine			
40	55	Clay, tan and brown			
55	75	Sand, med to coarse and med to coarse gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11 Nov 81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 11.8 Jun 82 under the business name of Central Well & Pump Inc. by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					