

USE TYPEWRITER OR BALL  
POINT PEN-PRESS FIRMLY,  
PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and  
Environment-Division of Environment  
(Water well Contractors)  
Topeka, Kansas 66620

1. Location of well:		County <b>Stafford</b>	Fraction <b>1/4 1/4CNW 1/4</b>	Section number <b>7</b>	Township number <b>T 25 S R 13</b>	Range number <b>EW</b>																															
2. Distance and direction from nearest town or city: <b>8 1/2 miles SW of St. John, KS</b> Street address of well location if in city:			3. Owner of well: <b>Robert Shank</b> R.R. or street: <b>Route 2</b> City, state, zip code: <b>St. John, KS 67576</b>																																		
4. Locate with "X" in section below: N W E S 1 Mile			Sketch map:		6. Bore hole dia. <b>24</b> in. Completion date <b>6-18-76</b> Well depth <b>130</b> ft.																																
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>5. Type and color of material</th> <th>From</th> <th>To</th> </tr> <tr> <td>sandy top soil</td> <td>0</td> <td>5</td> </tr> <tr> <td>brown &amp; gray clay</td> <td>5</td> <td>24</td> </tr> <tr> <td>sand &amp; clay streaks</td> <td>24</td> <td>29</td> </tr> <tr> <td>brown &amp; white clay &amp; limestone</td> <td>29</td> <td>44</td> </tr> <tr> <td>sand &amp; fine gravel &amp; clay streaks</td> <td>44</td> <td>50</td> </tr> <tr> <td>sand &amp; gravel</td> <td>50</td> <td>72</td> </tr> <tr> <td>brown clay &amp; limestone</td> <td>72</td> <td>95</td> </tr> <tr> <td>sand &amp; gravel</td> <td>95</td> <td>109</td> </tr> <tr> <td>brown clay</td> <td>109</td> <td>111</td> </tr> <tr> <td>sand &amp; gravel</td> <td>111</td> <td>130</td> </tr> </table>			5. Type and color of material	From	To	sandy top soil	0	5	brown & gray clay	5	24	sand & clay streaks	24	29	brown & white clay & limestone	29	44	sand & fine gravel & clay streaks	44	50	sand & gravel	50	72	brown clay & limestone	72	95	sand & gravel	95	109	brown clay	109	111	sand & gravel	111	130	7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary	
			5. Type and color of material	From	To																																
			sandy top soil	0	5																																
			brown & gray clay	5	24																																
			sand & clay streaks	24	29																																
			brown & white clay & limestone	29	44																																
			sand & fine gravel & clay streaks	44	50																																
			sand & gravel	50	72																																
			brown clay & limestone	72	95																																
			sand & gravel	95	109																																
brown clay	109	111																																			
sand & gravel	111	130																																			
8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																																					
9. Casing: Material <u>steel</u> Height <u>Above</u> or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface <u>12</u> in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight <u>30.3</u> lbs./ft. Dia. <u>16</u> in. to <u>50</u> ft. depth Wall Thickness: inches or Dia. <u>16</u> in. to <u>90</u> ft. depth gage No. <u>7 ga.</u>																																					
10. Screen: Manufacturer's name <u>Doerr</u> Type <u>Double-slot</u> Dia. <u>16"</u> Slot gauge <u>1/8"</u> Length <u>60'</u> Set between <u>50</u> ft. and <u>70</u> ft. <u>90</u> ft. and <u>130</u> ft. Gravel pack? <u>yes</u> Size range of material <u>3/8-200</u>																																					
11. Static water level: <u>16'</u> ft. below land surface Date <u>5-28-76</u> mo./day/yr.																																					
12. Pumping level below land surfaces: <u>N/C</u> <u>    </u> ft. after <u>    </u> hrs. pumping <u>    </u> g.p.m. <u>    </u> ft. after <u>    </u> hrs. pumping <u>    </u> g.p.m. Estimated maximum yield <u>    </u> g.p.m.																																					
13. Water sample submitted: <u>    </u> mo./day/yr. Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Date <u>    </u>																																					
14. Well head completion: <u>    </u> Pitless adapter <u>12</u> inches above grade																																					
15. Well grouted? <u>yes</u> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From <u>0</u> ft. to <u>10</u> ft.																																					
16. Nearest source of possible contamination: ft. <u>    </u> Direction <u>    </u> Type <u>    </u> Well disinfected upon completion? <u>    </u> Yes <input checked="" type="checkbox"/> No																																					
17. Pump: <u>Not installed</u> Manufacturer's name <u>FMC Corp/Peerless</u> Model number <u>12LB-3</u> HP <u>80</u> Volts <u>---</u> Length of drop pipe <u>70</u> ft. capacity <u>900</u> g.p.m. Type: <u>    </u> Submersible <input checked="" type="checkbox"/> Turbine <u>    </u> Jet <u>    </u> Reciprocating <u>    </u> Centrifugal <u>    </u> Other																																					
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <b>Clarke Well &amp; Eq. Inc.</b> <u>185</u> Business name License No. Address <u>Great Bend, KS 67530</u> Signed <u>P. W. Clarke</u> Date <u>6-23-76</u> Authorized representative																																	

25 130 7 1/4 1/4 1/4