

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: STAFFORD	NW 1/4 NW 1/4 SW 1/4	15	T 25 S	R 13 E/W

Distance and direction from nearest town or city street address of well if located within city?

14 1/2 N OF PRATT, KS

2 WATER WELL OWNER:	Ray Benintandi	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	RFD 2	Application Number:
City, State, ZIP Code :	St. John, Kansas	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 32 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr JAN 20 81 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 90 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 75 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel ③ RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC 4 ABS	7 Fiberglass		Threaded
Blank casing diameter 5 in. to 50 ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 2/4			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass ⑧ RMP (SR)	9 ABS	11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped ⑧ Saw cut	11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped	9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From 50 ft. to 55 ft., From ft. to ft.			
From 60 ft. to 75 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.			
From 14 ft. to 75 ft., From ft. to ft.			

6 GROUT MATERIAL: ① Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 14 ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well	
① Septic tank 4 Lateral lines 7 Pit privy	11 Fuel storage	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard	13 Insecticide storage		
Direction from well? S	How many feet? 70		

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	25	Clay, tan with fine sand			
25	30	Clay, blue			
30	33	Sand, fine to med			
33	45	Clay, green			
45	56	Sand, fine to med and fine to med gravel			
56	60	Clay, brown			
60	74	Sand, med to coarse and med to coarse gravel, loose			
74	90	Clay, brown and white			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) JAN 23 81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) JULY 4 81 under the business name of Central Well & Pump Inc. Pratt, Kansas by (signature) <i>Edithonovich</i>
--

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.