

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 72 ft. ELEVATION: 2900 ft.

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

5	TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped Welded Threaded
	1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	
	2 PVC	4 ABS	7 Fiberglass		

TYPE OF SCREEN OR PERFORATION MATERIAL:			☒ 7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN-PERFORATED INTERVALS:	From	62	ft. to	72	ft.	From		ft. to		ft.
	From		ft. to		ft.	From		ft. to		ft.
GRAVEL PACK INTERVALS:	From	20	ft. to	72	ft.	From		ft. to		ft.
	From		ft. to		ft.	From		ft. to		ft.

What is the nearest source of possible contamination:					10 Livestock pens	14 Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	none		

[illegible]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.