WATE	R WEI	L RECORD	Form V	Division of Wate	r Resources App. No	o.		
1 LOCATION OF WATER WELL:			Fraction		Section Number		Range Number	
County: Stafford				E 1/4 SE 1/4	Clabal Pacition in a	T 25 S	R 14 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					Global Positioning System (GPS) information:  Latitude:			
6 South, 1 1/2 West of St. John					Longitude: (in decimal degrees)			
o double, i the troot of our continu					Elevation:			
2 WATER WELL OWNER: Alan Campbell					Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 263 Coleman Loop					GPS unit (Make/Model:)			
City.	, State, Z	IP Code : Homer,	LA 71040		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Surv Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .76 ft.								
SECTION BOX:  N  Depth(s) Groundwater Encountered (1)							3) ft.	
Pump test data: Well water wasft. after							oing gpm	
EST. YIELD. N/Agpm. Well water was							ping gpm	
W         E   Bore Hole Diameter !!								
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)								
SV	SW   SE							
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No								
S If yes, mo/day/yr sample was submitted								
water wert districted: Ly Tes 140								
5 TYPE OF CASING USED: Steel V PVC Other								
Casing diameter								
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.								
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From						ft. 1	to ft.	
GRAVEL PACK INTERVALS: From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout In		From ft. to		om .20	ft. to .0 ft.,	From	. ft. toft.	
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well								
□ Watertight sewer lines □ Seepage pit □ Feedyard □ Fertilizer storage ▼ Oil well/gas well								
FROM	TO TO	LITHOLOG	IC LOG	FROM		OG (cont.) or PLU	GGING INTERVALS	
0	3	Sandy top soil	10 100	11014	. Diffio. Et	oc (cont.) or 1 DO	COMO MILICANES	
3	11	Clay						
11	30	Sand & gravel						
30 35	35 68	Clay Sand & gravel					24	
68	76	Clay						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .10-16-14 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 10-21-14								
under the business name of Rosencrantz-Bemis Ent Inc by (signature) Communication (signature) Communication (signature) Rosencrantz-Bemis Ent Inc by (signature) Rosencrantz-Bemis Ent Inc Bemis								
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check:   ☐ White Copy, ☐ Blue Copy, ☐ Pink Copy								