

1 LOCATION OF WATER WELL: County: Stafford	Fraction 1/4 1/4 NE 1/4	Near Center of	Section Number 1	Township Number T 25 S	Range Number R 14 E/W
---	----------------------------	----------------	---------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?
Approx. 5 3/4 miles south and 3 1/4 miles west of St. John, KS

2 WATER WELL OWNER:	David McCandless	
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	St. John, KS 67576	Application Number: 31,535

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL. 113 ft. ELEVATION: unknown

Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 3/18/87

Pump test data: Well water was not ck'd. ft. after hours pumping gpm

Est. Yield 1000 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter. 24 in. to 113 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
10 Observation well		

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded ^{xxxx}
2 PVC	4 ABS	7 Fiberglass		Threaded

Blank casing diameter . . 16 in. to . . 47 ft., Dia . . 16 in. to . 92 ft., Dia in. to ft.

Casing height above land surface 12 in., weight 36, 87 lbs./ft. Wall thickness or gauge No. . . . 219

TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
5 Fiberglass	6 Concrete tile		

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify) , 100 Slot Johnson Agr	

SCREEN-PERFORATED INTERVALS:

From 47 ft. to . . 67 ft., From ft. to ft.
From 92 ft. to . . 112 ft., From ft. to ft.

GRAVEL PACK INTERVALS:

From 30 ft. to . . 112 ft., From ft. to ft.
Annular Fill From 10 ft. to . . 30 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	FIELD

Direction from well? all How many feet?

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/18/87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 3/19/87 under the business name of Clarke Well & Equipment, Inc. by (signature) 

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.