

1 LOCATION OF WATER WELL: County: Stafford		Fraction C 1/4 S 1/2 NW 1/4	Section Number 13	Township Number T 25 S	Range Number R 14 E
--	--	---------------------------------------	-----------------------------	----------------------------------	-------------------------------

[illegible]

From St. John, Ks. 8 1/4 south, 2 3/4 West

2	WATER WELL OWNER:	Emphasis Oil	
	RR#, St. Address, Box # :	Box 506	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Russell, Ks. 67665	Application Number: 920224

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W E

N S

SW NW NE SE

4) DEPTH OF COMPLETED WELL. 80 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr 6-25-92

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield na gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to 80 ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		9 Dewatering
		10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes b+h No

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued .X. Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded	
2 PVC	4 ABS	7 Fiberglass		Threaded	
Blank casing diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 2' in., weight 258 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement	
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)	
			9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes		
		7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS:					
	From 60 ft. to 80 ft., From ft. to ft.				
	From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS:					
	From 20 ft. to 80 ft., From ft. to ft.				
	From ft. to ft., From ft. to ft.				

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 <u>Bentonite</u>	4 Other	hole plug
Grout Intervals:		From 0 ft. to 20 ft.	From	ft. to	ft.	From
What is the nearest source of possible contamination:						
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well		
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 <u>Oil well/Gas well</u>		
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)		
Direction from well?			south			
			How many feet?		100	

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-25-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 7-2-92 under the business name of Rosencrantz-Bemis by (signature) [Signature]