


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County: <u>Stafford</u>	Fraction: <u>1/4 C 1/4 NW 1/4</u>	Section number: <u>28</u>	Township number: T <u>25</u> S	Range number: R <u>14</u> E <u>W</u>
2. Distance and direction from nearest town or city: <u>50 Hwy # Dillwin, KS rd. 8 1/4 mi So.</u> Street address of well location if in city: <u>East side of road.</u>			3. Owner of well: <u>Richard Waters</u> R.R. or street: <u>704 N. Nutting</u> City, state, zip code: <u>St. John, KS 67576</u>		
4. Locate with "X" in section below: N  S E W 1 Mile			6. Bore hole dia. <u>2 1/2</u> in. Completion date: <u>5-12-77</u> Well depth <u>130</u> ft.		
			7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
			8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☒ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other		
			9. Casing: Material <u>steel</u> Height: Above or below Threaded ☐ Welded ☒ Surface <u>18</u> in. RMP ☐ PVC ☐ Weight ☐ lbs./ft. Dia. <u>1 1/2</u> in. to <u>130</u> ft. depth Wall Thickness: inches or Dia. ☐ in. to ☐ ft. depth gage No. <u>7</u>		
5. Type and color of material			From	To	10. Screen: Manufacturer's name <u>Doerr's</u> Type <u>steel</u> Dia. <u>60'</u> Slot/gauge <u>3/16</u> Length <u>60'</u> Set between <u>70</u> ft. and <u>130</u> ft. Gravel pack? ☒ Size range of material <u>2 1/4 to 3/8</u>
<u>Sandy top soil</u>			<u>0</u>	<u>3</u>	11. Static water level: <u>12</u> ft. below land surface Date <u>2-22-77</u> mo./day/yr.
<u>Brown clay</u>			<u>3</u>	<u>11</u>	12. Pumping level below land surfaces: <u>31</u> ft. after <u>1</u> hrs. pumping <u>600</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>1400</u> g.p.m.
<u>Gray clay</u>			<u>11</u>	<u>13</u>	13. Water sample submitted: <u>X</u> Yes <u> </u> No Date <u>2-22-77</u> mo./day/yr.
<u>Brown clay</u>			<u>13</u>	<u>21</u>	14. Well head completion: <u> </u> Pitless adapter <u> </u> Inches above grade
<u>White clay</u>			<u>21</u>	<u>24</u>	15. Well grouted? ☒ With: ☒ Neat cement <u> </u> Bentonite <u> </u> Concrete Depth: From <u>0</u> ft. to <u>10</u> ft.
<u>Brown clay</u>			<u>24</u>	<u>38</u>	16. Nearest source of possible contamination: ft. <u>1200</u> Direction <u>SW</u> Type <u>oil well</u> Well disinfected upon completion? <u> </u> Yes <u> </u> No
<u>Sand & gravel</u>			<u>38</u>	<u>63</u>	17. Pump: Manufacturer's name <u>Layne Bowler</u> Not installed Model number <u>610BH</u> HP <u>40</u> Volts <u> </u> Length of drop pipe <u>60</u> ft. capacity <u>800</u> g.p.m. Type: <u> </u> Submersible ☒ Turbine <u> </u> Jet <u> </u> Reciprocating <u> </u> Centrifugal <u> </u> Other
<u>Yellow brown white clay</u>			<u>63</u>	<u>69</u>	
<u>Sand & gravel brown clay mix</u>			<u>69</u>	<u>72</u>	
<u>Sand & gravel</u>			<u>72</u>	<u>78</u>	
<u>Brown clay</u>			<u>78</u>	<u>80</u>	
<u>Sand & gravel</u>			<u>80</u>	<u>100</u>	
<u>Brown & gray clay</u>			<u>100</u>	<u>110</u>	
<u>Sand & gravel</u>			<u>110</u>	<u>158</u>	
<u>Brown clay</u>			<u>158</u>	<u>160</u>	
(Use a second sheet if needed)					
18. Elevation:	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Rosemary-Bemis</u> <u>134</u> Business name License No. Address <u>4001 Bend, KS 67530</u> Signed <u>Shirley Kilgore</u> Date <u>5-17-77</u> Authorized representative		
Topography: <u> </u> Hill <u> </u> Slope ☒ Upland <u> </u> Valley					

25 140 28 1/4 1/4 C NW