

1 LOCATION OF WATER WELL:		Fraction	SE 1/4	SE 1/4	NW 1/4	Section Number	12	Township Number	T 25 S	Range Number	R 15 E/W
County: STAFFORD											
Distance and direction from nearest town or city street address of well if located within city?											
4-S. 2 1/2 E. OF MACKSVILLE,KS.											
2 WATER WELL OWNER: FRED GRUNDER											
RR#, St. Address, Box # : 122 S. MAIN											
City, State, ZIP Code : ST. JOHN, KS. 67576											
Board of Agriculture, Division of Water Resources											
Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:											
4 DEPTH OF COMPLETED WELL: 68 ft. ELEVATION:											
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.											
WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr											
Pump test data: Well water was ft. after hours pumping gpm											
Est. Yield gpm: Well water was ft. after hours pumping gpm											
Bore Hole Diameter 9 in. to ft., and in. to ft.											
WELL WATER TO BE USED AS:											
5 Public water supply 8 Air conditioning 11 Injection well											
XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)											
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes X No											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped											
XX PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded											
7 Fiberglass Threaded											
Blank casing diameter 5 in. to 58 ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No.											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
XX PVC 10 Asbestos-cement											
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)											
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot XX Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)											
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes											
7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 58 ft. to 68 ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From 23 ft. to 68 ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout XX Bentonite 4 Other											
Grout Intervals: From 3 ft. to 23 ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)											
NONE											
Direction from well? How many feet?											
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS											
0 3 TOP SOIL											
3 50 CLAY & SAND STREAKS											
50 68 GRAVEL											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-29-92 and this record is true to the best of my knowledge and belief. Kansas											
Water Well Contractor's License No. 462-B This Water Well Record was completed on (mo/day/yr) 4-2-93											
under the business name of SAM'S WATER WELL SERVICE by (signature)											