

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County:	Stafford	NE 1/4 NE 1/4 NE 1/4	34	T 25 S	R 15W E/W

Distance and direction from nearest town or city street address of well if located within city?

9 S, $\frac{1}{4}$ E of Macksville, Kansas

2	WATER WELL OWNER:	Jim Johnson	
	RR#, St. Address, Box # :	Route 1	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Macksville, Kansas 67557	Application Number: None

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4	DEPTH OF COMPLETED WELL.....	80	ft. ELEVATION:	Unknown
				19		

1 Mile
W

NW

NE

SW

SE

E

Depth(s) Groundwater Encountered 1. 17 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 9/11/81

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 60 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to 80 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply

8 Air conditioning

11 Injection well

1 Domestic

3 Feedlot

6 Oil field water supply

9 Dewatering

12 Other (Specify below)

2 Irrigation

4 Industrial

7 Lawn and garden only

10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5	TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: <u>Glued</u> Clamped Welded Threaded
	1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	
	2 PVC	4 ABS	7 Fiberglass		

Blank casing diameter . . . 5 . . . in. to . . . 60 . . . ft., Dia . . . in. to . . . ft., Dia . . . in. to . . . ft.
Casing height above land surface . . . 12 . . . in., weight . . . 2.8 . . . lbs./ft. Wall thickness or gauge No. . . Sch. 40 . . . ft.

TYPE OF SCREEN OR PERFORATION MATERIAL:			7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 <u>Saw cut</u>	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS:	From 60 ft. to 80 ft.	From 80 ft. to 100 ft.	From 100 ft. to 120 ft.	From 120 ft. to 140 ft.	From 140 ft. to 160 ft.	From 160 ft. to 180 ft.	From 180 ft. to 200 ft.	From 200 ft. to 220 ft.	From 220 ft. to 240 ft.	From 240 ft. to 260 ft.	From 260 ft. to 280 ft.	From 280 ft. to 300 ft.	From 300 ft. to 320 ft.	From 320 ft. to 340 ft.	From 340 ft. to 360 ft.	From 360 ft. to 380 ft.	From 380 ft. to 400 ft.	From 400 ft. to 420 ft.	From 420 ft. to 440 ft.	From 440 ft. to 460 ft.	From 460 ft. to 480 ft.	From 480 ft. to 500 ft.	From 500 ft. to 520 ft.	From 520 ft. to 540 ft.	From 540 ft. to 560 ft.	From 560 ft. to 580 ft.	From 580 ft. to 600 ft.	From 600 ft. to 620 ft.	From 620 ft. to 640 ft.	From 640 ft. to 660 ft.	From 660 ft. to 680 ft.	From 680 ft. to 700 ft.	From 700 ft. to 720 ft.	From 720 ft. to 740 ft.	From 740 ft. to 760 ft.	From 760 ft. to 780 ft.	From 780 ft. to 800 ft.	From 800 ft. to 820 ft.	From 820 ft. to 840 ft.	From 840 ft. to 860 ft.	From 860 ft. to 880 ft.	From 880 ft. to 900 ft.	From 900 ft. to 920 ft.	From 920 ft. to 940 ft.	From 940 ft. to 960 ft.	From 960 ft. to 980 ft.	From 980 ft. to 1000 ft.
GRAVEL PACK INTERVALS:	From 10 ft. to 80 ft.	From 80 ft. to 100 ft.	From 100 ft. to 120 ft.	From 120 ft. to 140 ft.	From 140 ft. to 160 ft.	From 160 ft. to 180 ft.	From 180 ft. to 200 ft.	From 200 ft. to 220 ft.	From 220 ft. to 240 ft.	From 240 ft. to 260 ft.	From 260 ft. to 280 ft.	From 280 ft. to 300 ft.	From 300 ft. to 320 ft.	From 320 ft. to 340 ft.	From 340 ft. to 360 ft.	From 360 ft. to 380 ft.	From 380 ft. to 400 ft.	From 400 ft. to 420 ft.	From 420 ft. to 440 ft.	From 440 ft. to 460 ft.	From 460 ft. to 480 ft.	From 480 ft. to 500 ft.	From 500 ft. to 520 ft.	From 520 ft. to 540 ft.	From 540 ft. to 560 ft.	From 560 ft. to 580 ft.	From 580 ft. to 600 ft.	From 600 ft. to 620 ft.	From 620 ft. to 640 ft.	From 640 ft. to 660 ft.	From 660 ft. to 680 ft.	From 680 ft. to 700 ft.	From 700 ft. to 720 ft.	From 720 ft. to 740 ft.	From 740 ft. to 760 ft.	From 760 ft. to 780 ft.	From 780 ft. to 800 ft.	From 800 ft. to 820 ft.	From 820 ft. to 840 ft.	From 840 ft. to 860 ft.	From 860 ft. to 880 ft.	From 880 ft. to 900 ft.	From 900 ft. to 920 ft.	From 920 ft. to 940 ft.	From 940 ft. to 960 ft.	From 960 ft. to 980 ft.	From 980 ft. to 1000 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 <u>Septic tank</u>	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 <u>Sewer lines</u>	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? East			13 Insecticide storage	
			How many feet? 150	

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/11/81 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 186. This Water Well Record was completed on (mo/day/yr) 10/29/81

under the business name of Kellys Water Wells by (signature) Deon Reed

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.