

WATER WELL RECORD										Form WWC-5		KSA 82a-1212	
1 LOCATION OF WATER WELL:			Fraction			Section Number		Township Number		Range Number			
County: Stafford			NE 1/4 NE 1/4 NE 1/4			15		T 25 S		R 15W E/W			
Distance and direction from nearest town or city street address of well if located within city?													
1 E, 5 S of Macksville, Kansas													
2 WATER WELL OWNER:		Doyle Wilson				Sterling Drilling Co.				Wilson H-1			
RR#, St. Address, Box # :		Route 1				Box 129				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Macksville, Ks. 67557				Sterling, Ks. 67579				Application Number: 940476			

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N				

4 DEPTH OF COMPLETED WELL: 116 ft. ELEVATION: Unknown

Depth(s) Groundwater Encountered 1. 43 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 43 ft. below land surface measured on mo/day/yr 11/29/94

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 60 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 7 7/8 in. to 116 ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 <u>Oil field water supply</u>
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

9 Dewatering 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:		3 Wrought iron	8 Concrete tile	CASING JOINTS: <u>Glued</u>	<u>Clamped</u>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	<u>Welded</u>	
2 <u>PVC</u>	4 ABS	7 Fiberglass		<u>Threaded</u>	
Blank casing diameter . . . 5 . . . in. to . . . 96 . . . ft., Dia		. . . in. to . . . ft., Dia		. . . in. to . . . ft.	
Casing height above land surface 12 . . . in., weight . . . 2.8 . . . lbs./ft.		Wall thickness or gauge No.		<u>Sch.</u> . . 40 . . .	
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel	3 Stainless steel	5 Fiberglass	7 <u>PVC</u>	10 Asbestos-cement	
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)	
			9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 <u>Saw cut</u>	11 None (open hole)	
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes		
		7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From 96 ft. to . . . 116 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to . . . 116 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					

6] GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:		From . . . 0 ft. to . . 20 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.
What is the nearest source of possible contamination:				10 Livestock pens	14 Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage		
Direction from well?		South	How many feet?	60	

[illegible]

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/29/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 11/30/94 under the business name of Kelly's Water Well Service, Inc. by (signature) [Signature]