

1 LOCATION OF WATER WELL: County: EDWARDS Fraction: W 1/2 E 1/2 SE 1/4 Section Number: 17 Township Number: T 25 S Range Number: R 16 E 10

Distance and direction from nearest town or city street address of well if located within city: TROUSDALE 1/2 N 1/2 W 3/4 N WESTSIDE

2 WATER WELL OWNER: STERLING DRILLING CO. MR. SETTE, TROUSDALE, KS

RR#, St. Address, Box #: BOX 129 Board of Agriculture, Division of Water Resources

City, State, ZIP Code: STERLING, KS 67579 Application Number: T84-57

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: 44 ft.

WELL'S STATIC WATER LEVEL: 24 ft. below land surface measured on mo/day/yr 12-23-83

Pump test data: Well water was 3 ft. after 3 hours pumping 3 gpm

Est. Yield: 3 gpm Well water was 3 ft. after 3 hours pumping 3 gpm

Bore Hole Diameter: 77/8 in. to 75 ft. and 75 in. to 75 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter: 5 in. to 55 ft. Dia. 55 in. to 55 ft. Dia. 55 in. to 55 ft. Dia.

Casing height above land surface: 12 in. weight 7.65 lbs./ft. Wall thickness or gauge No. 2.14

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 18

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 55 ft. to 75 ft. From 55 ft. to 75 ft. From 55 ft. to 75 ft.

GRAVEL PACK INTERVALS: From 24 ft. to 75 ft. From 24 ft. to 75 ft. From 24 ft. to 75 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.

What is the nearest source of possible contamination: NONE

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	8	CLAY			
8	18	SANDY CLAY			
18	28	FINE SAND			
28	38	SANDY CLAY			
38	43	CLAY			
43	75	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-23-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 12-29-83 under the business name of REISER WATER WELL SERV. INC. by (signature) Rudolph Reiser

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline of circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.